



COMPO L WALLWASH SOFT 930

9 15740 9000 C


AVAILABLE IN
CHROMED 9 15740 9000 C
WHITE 9 15740 9000 W



EXCLUSIVELY AVAILABLE IN INDIA



0-30°/355°



 [View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 135
RECESSED DEPTH (MM)	130
THICKNESS OF MOUNTING SURFACE (MM)	max.25
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.462
ADJUSTABILITY	0° to 30° swiveling, 355° rotatable
Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	F
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 20,1W / CRI>90 / 3000K-1800K / 2264lm
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	NA
LED TECHNICS (LIGHT SOURCE)	2264lm // 20,1W // 112lm/W
LED TECHNICS (LUMINAIRE)	715lm // 23,1W // 31lm/W
Requirements	
LED POWER SUPPLY 600 mA - DC	

For detailed installation instructions, please consult the manual : [9_15740_XXX0_HAND.pdf](#)

DELTALIGHT

COMPO L WALLWASH SOFT 930

9 15740 9000 C

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
	 15710 0030 - MOUNTING KIT COMPO L TRIM	Required
	 15710 0060 - MOUNTING KIT COMPO L TRIMLESS	Required
	 15710 0030 - MOUNTING KIT COMPO L TRIM	Required
	 15710 0060 - MOUNTING KIT COMPO L TRIMLESS	Required
	 15710 0030 - MOUNTING KIT COMPO L TRIM	Required
	 15710 0060 - MOUNTING KIT COMPO L TRIMLESS	Required

FINISH YOUR SPECIFICATION

LED Power supply

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current

15710 4300

LED POWER SUPPLY MULTIPOWER 30W DIM8 600mA

1

15710 4800

LED POWER SUPPLY MULTIPOWER 20W DIM1 600mA

1

15710 5500

LED POWER SUPPLY MULTIPOWER 20W DALI DT6 600mA

1

Dimtype: DALI

Mounting kits



15710 0030 B MOUNTING KIT COMPO L TRIM B

Cutout dimension (mm): 92

15710 0030 W MOUNTING KIT COMPO L TRIM W



15710 0060 MOUNTING KIT COMPO L TRIMLESS

Cutout dimension (mm): 92

DELTALIGHT

COMPO L WALLWASH SOFT 930

9 15740 9000 C

Notes: