





Image may differ from the actual product
Consult drawing for correct size and structure

INFORM 40 SQ 360 DOWN TW 1 DT8 85063 DIM5

30718 8035 B-B

DISPONIBLE EN
NOIR-NOIR 30718 8035 B-B
BLANC-NOIR 30718 8035 W-B



 [Voir sur le site Web](#)



Informations générales	
EMPLACEMENT	interieur
INSTALLATION	Plafond Applique,Plafond Suspendu
INDICE DE PROTECTION	IP20
POIDS (KG)	5.6
ORIENTATION	non réglable
INFORMATIONS	INCL.DIMMABLE LED POWER SUPPLY (DALI DT8) EXCL.CABLE SUSPENSION MELANOPIC LIGHT TECHNOLOGY
Informations électriques	
ÉLECTRIQUE	220-240V / 0 50-60Hz
CLASSE	I
ALIMENTATION	YES
TYPE DIM	DALI
CLASSE D'ÉNERGIE	E
Info Source lumineuse	
LIGHTSOURCE NAME	LED
SOURCE DE LUMIÈRE	@ 2700K: LED cluster 29,8W / CRI>80 (R9: 50) / 2700K-5000K / 3904lm Or @ 5000K: LED cluster 27W / CRI>80 (R9: 50) / 2700K-5000K / 4672lm
SDCM	SDCM3
GROUPE DE RISQUE	RG1
BEAMANGLE	63°
TECHNIQUES LED (SOURCE LUMINEUSE)	@ 2700K: 3904lm // 29,8W // 131lm/W Or @ 5000K: 4672lm // 27W // 173lm/W
TECHNIQUES LED (LUMINAIRE)	@ 2700K: 2701lm // 34,3W // 79lm/W Or @ 5000K: 3233lm // 31W // 104lm/W
Références optionnelles	

INF40 SQ 320/360 - SUSPENSION SET
CABLE BASE R / S

Pour des instructions d'installation détaillées, veuillez consulter le manuel : [30718_XXX5_HAND.pdf](#)

DELTALIGHT

INFORM 40 SQ 360 DOWN TW 1 DT8 85063 DIM5

30718 8035 B-B

TERMINEZ VOTRE SPÉCIFICATION

le cable d'alimentation



203 99 55 ANO CABLE BASE R ANO

203 99 55 B CABLE BASE R B

203 99 55 W CABLE BASE R W




203 99 56 ANO CABLE BASE S ANO

203 99 56 B CABLE BASE S B


203 99 56 W CABLE BASE S W

les accessoires de fixations



30710 0020 B INF40 SQ 320/360 - SUSPENSION SET 1,6m B

30710 0020 W INF40 SQ 320/360 - SUSPENSION SET 1,6m W



30710 0040 B INF40 SQ 320/360 - SUSPENSION SET 3,0m B

30710 0040 W INF40 SQ 320/360 - SUSPENSION SET 3,0m W

DELTALIGHT

INFORM 40 SQ 360 DOWN TW 1 DT8 85063 DIM5

30718 8035 B-B

Notes: