




Image may differ from the actual product
Consult drawing for correct size and structure

**INFORM 40 SQ 360 DOWN TW 1
DT8 85063 DIM5**

30718 8035 B-B

AVAILABLE IN
BLACK-BLACK 30718 8035 B-B
WHITE-BLACK 30718 8035 W-B



 [View on website](#)




General info	
LOCATION	indoor
INSTALLATION	Ceiling Surface mounted,Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	5.6
ADJUSTABILITY	non adjustable
INFORMATION	INCL.DIMMABLE LED POWER SUPPLY (DALI DT8) EXCL.CABLE SUSPENSION MELANOPIC LIGHT TECHNOLOGY
Electrical info	
ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	E
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	@ 2700K: LED cluster 29,8W / CRI>80 (R9: 50) / 2700K-5000K / 3904lm Or @ 5000K: LED cluster 27W / CRI>80 (R9: 50) / 2700K-5000K / 4672lm
SDCM	SDCM3
RISKGROUP	RG1
BEAMANGLE	63°
LED TECHNICS (LIGHT SOURCE)	@ 2700K: 3904lm // 29,8W // 131lm/W Or @ 5000K: 4672lm // 27W // 173lm/W
LED TECHNICS (LUMINAIRE)	@ 2700K: 2701lm // 34,3W // 79lm/W Or @ 5000K: 3233lm // 31W // 104lm/W
Options	
INF40 SQ 320/360 - SUSPENSION SET CABLE BASE R / S	

For detailed installation instructions, please consult the manual : [30718_XXX5_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Current supply

	☐	203 99 55 ANO CABLE BASE R ANO	☐
		203 99 55 B CABLE BASE R B	☐
		203 99 55 W CABLE BASE R W	☐
	☐	203 99 56 ANO CABLE BASE S ANO	☐
		203 99 56 B CABLE BASE S B	☐
		203 99 56 W CABLE BASE S W	☐

Fixation components

	☐	30710 0020 B INF40 SQ 320/360 - SUSPENSION SET 1,6m B	☐
		30710 0020 W INF40 SQ 320/360 - SUSPENSION SET 1,6m W	☐
	☐	30710 0040 B INF40 SQ 320/360 - SUSPENSION SET 3,0m B	☐
		30710 0040 W INF40 SQ 320/360 - SUSPENSION SET 3,0m W	☐

DELTALIGHT

INFORM 40 SQ 360 DOWN TW 1 DT8 85063 DIM5

30718 8035 B-B

Notes: