
DELTALIGHT




SUPERNOVA FLAT 65 DOWN-UP 930

REFERENCE 20612 9300 B

AVAILABLE IN
BLACK 20612 9300 B
WHITE 20612 9300 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	9.2
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC SBL INCL.ADJUSTABLE LED POWER SUPPLY 500mA UP / DOWN - 2 settings: 1- 1400mA 2- 930mA

Electrical info	
ELECTRICAL	220-240V / 0|50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, LCA, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN @ 1400mA: LED cluster 58,5W / CRI>90 (R9: 68) / 3000K / 7776lm UP @ 500mA: 2 x (LED cluster 11,1W / CRI>90 (R9: 50) / 3000K / 1487lm) Or DOWN @ 930mA: LED cluster 37,4W / CRI>90 (R9: 68) / 3000K / 5360lm UP @ 500mA: 2 x (LED cluster 11,1W / CRI>90 (R9: 50) / 3000K / 1487lm)
TM-30 VALUES	Rf: 89 / Rg: 97 Rf: 92 / Rg: 100 DOWN @ 930mA: Rf: 89 / Rg: 97 UP @ 500mA: Rf: 92 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG1 RG0
LM80	L70 > 60000 L80 > 60000
LED TECHNICS (LIGHT SOURCE)	DOWN @ 1400mA: 7776lm // 58,5W // 132lm/W UP @ 500mA: 2974lm // 22,2W // 134lm/W Or DOWN @ 930mA: 5360lm // 37,4W // 144lm/W UP @ 500mA: 2974lm // 22,2W // 134lm/W
LED TECHNICS (LUMINAIRE)	DOWN @ 1400mA: 5925lm // 67,3W // 88lm/W UP @ 500mA: 2784lm // 25,5W // 109lm/W Or DOWN @ 930mA: 4084lm // 43W // 95lm/W UP @ 500mA: 2784lm // 25,5W // 109lm/W

DELTALIGHT

SUPERNOVA FLAT 65 DOWN-UP 930

20612 9300 B

Requirements

SUSPENSION SET 25 3m
CENTRAL ROD SUSPENSION SUPERNOVA FLAT 1m
CENTRAL SUSPENSION SUPERNOVA FLAT


Options

CABLE BASE R / S
COVERSET R 62-90-100 / S 62-80-90

For detailed installation instructions, please consult the manual : **20612_XXX0_HAND.pdf**

FINISH YOUR SPECIFICATION

Current supply



203 99 55 ANO CABLE BASE R ANO ☐

203 99 55 B CABLE BASE R B ☐

203 99 55 W CABLE BASE R W ☐




203 99 56 ANO CABLE BASE S ANO ☐

203 99 56 B CABLE BASE S B ☐

203 99 56 W CABLE BASE S W ☐

Coversets








204 00 62 ANO COVERSET R 62 ANO ☐

204 00 62 B COVERSET R 62 B ☐

SUPERNOVA FLAT 65 DOWN-UP 930

20612 9300 B


	204 00 62 W	COVERSET R 62 W
	**204 00 90 ANO**	COVERSET R 90 ANO
	204 00 90 B	COVERSET R 90 B
	204 00 90 W	COVERSET R 90 W
	**204 00 100 ANO**	COVERSET R 100 ANO
	204 00 100 B	COVERSET R 100 B
	204 00 100 W	COVERSET R 100 W
	**204 62 62 ANO**	COVERSET S 62 ANO
	204 62 62 B	COVERSET S 62 B
	204 62 62 W	COVERSET S 62 W
	**204 80 80 ANO**	COVERSET S 80 ANO
	204 80 80 B	COVERSET S 80 B
	204 80 80 W	COVERSET S 80 W
	**204 90 90 ANO**	COVERSET S 90 ANO
	204 90 90 B	COVERSET S 90 B

SUPERNOVA FLAT 65 DOWN-UP 930

20612 9300 B


204 90 90 W COVERSET S 90 W

Suspension parts




274 97 10 B CENTRAL ROD SUSPENSION SUPERNOVA FLAT 1m B

274 97 10 W CENTRAL ROD SUSPENSION SUPERNOVA FLAT 1m W



328 25 43 SUSPENSION SET 25 3m



328 26 23 B CENTRAL SUSPENSION SUPERNOVA FLAT 3m B

328 26 23 W CENTRAL SUSPENSION SUPERNOVA FLAT 3m W

Electric connection parts



15225 0360 B CONNECTION ST B

Cutout dimension (mm): 43

15225 0360 W CONNECTION ST W

Notes: