



LOGIC LINEAR 880 92715

30820 9210 INOX

AVAILABLE IN  
INOX 30820 9210 INOX



[View on website](#)



|                                      |                                                                                                                                               |
|--------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|
| General info                         |                                                                                                                                               |
| LOCATION                             | outdoor                                                                                                                                       |
| INSTALLATION                         | Floor Recessed                                                                                                                                |
| CUTOUT SHAPE/SIZE (MM)               | rectangle - BOX                                                                                                                               |
| RECESSED DEPTH (MM)                  | 140                                                                                                                                           |
| INGRESS PROTECTION                   | IP67                                                                                                                                          |
| PROTECTION AGAINST MECHANICAL IMPACT | IK09                                                                                                                                          |
| WEIGHT (KG)                          | 4.4                                                                                                                                           |
| ADJUSTABILITY                        | non adjustable                                                                                                                                |
| INFORMATION                          | 16 x LENS SP-15°<br>INCL.LED POWER SUPPLY 650mA-DC<br>INCL.1 x CABLE H05 RN-F 3 x 0.75mm² 0,5m<br>INCL.IP68 CONNECTOR 3P<br>ESG 8mm max.500kg |
| Electrical info                      |                                                                                                                                               |
| ELECTRICAL                           | 220-240V / 0 50-60Hz                                                                                                                          |
| CLASS                                | I                                                                                                                                             |
| POWER SUPPLY                         | YES                                                                                                                                           |
| DIM TYPE                             | non-dimmable                                                                                                                                  |
| ENERGY CLASS                         | F                                                                                                                                             |
| CERTIFICATES                         | CB, ENEC, EPD, RCM                                                                                                                            |
| Lightsource info                     |                                                                                                                                               |
| LIGHTSOURCE NAME                     | LED                                                                                                                                           |
| LIGHTSOURCE                          | LED cluster 28,8W / CRI>90 (R9: 55) / 2700K / 3288lm                                                                                          |
| TM-30 VALUES                         | Rf: 91 / Rg: 100                                                                                                                              |
| SDCM                                 | SDCM3                                                                                                                                         |
| RISKGROUP                            | RG2                                                                                                                                           |
| LM80                                 | L80 > 150000                                                                                                                                  |
| BEAMANGLE                            | 15°                                                                                                                                           |
| LED TECHNICS (LIGHT SOURCE)          | 3288lm // 28,8W // 111lm/W                                                                                                                    |
| LED TECHNICS (LUMINAIRE)             | 2433lm // 33,1W // 73lm/W                                                                                                                     |
| Requirements                         |                                                                                                                                               |
| LOGIC LINEAR BOX                     |                                                                                                                                               |

For detailed installation instructions, please consult the manual : [30820\\_XXX0\\_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Ground mounting boxes



**30810 0030** LOGIC LINEAR 880 BOX

☐

Cutout dimension (mm): 920 x 150

Waterproof connection parts



**431 99 02** IP68 JUNCTION BOX 4P

☐

**21034 0150** IP68 Y-CONNECTOR 5P

☐

Notes: