




SUPERLOOP-SPY 52 93045 MDL
20567 9330 FG

AVAILABLE IN
BLACK 20567 9330 B
FLEMISH BRONZE 20567 9330 FBR
FLEMISH GOLD 20567 9330 FG
GOLD COLOURED 20567 9330 GC
WHITE 20567 9330 W



 [View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.4
ADJUSTABILITY	0° to 90° swiveling, 355° rotatable
INFORMATION	REFLECTOR WFL-45° INCL.CLIP 48V ADAPTER EXCL.LED POWER SUPPLY 48V-DC Optional REFLECTORS 20° & 30° available

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1-10V or DALI or push button
ENERGY CLASS	D
CERTIFICATES	CB, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1089lm
TM-30 VALUES	Rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	45°
LED TECHNICS (LIGHT SOURCE)	1089lm // 8,6W // 127lm/W
LED TECHNICS (LUMINAIRE)	697lm // 9,9W // 70lm/W

Requirements	
SPY 52 TUBE	
LED POWER SUPPLY 48V-DC	

Options	
DIMMABLE MODULATOR	

Accessories	
HONEYCOMB 42	
SPREAD LENS 42	
LINEAR SPREAD LENS 42	
SOFTENING LENS 42	

SUPERLOOP-SPY 52 93045 MDL

20567 9330 FG

GLASS SBL 42

For detailed installation instructions, please consult the manual : [20567_XXX0_HAND.pdf](#)


FINISH YOUR SPECIFICATION

SMART 48

of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



300 90 011 SMART 48 MODULATOR DIM9

19

Dimtype: 1-10V or DALI or push button



300 90 012 SMART 48 MODULATOR WD

19


Dimtype: WDL = wireless dimmable

LED power supplies

of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

10


Dimtype: non-dimmable



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN

24

Dimtype: non-dimmable



21012 0230 LED POWER SUPPLY 48V-DC / 100W

10

Dimtype: non-dimmable

Cutout dimension (mm): 40

DELTALIGHT

SUPERLOOP-SPY 52 93045 MDL

20567 9330 FG




21012 0240 LED POWER SUPPLY 48V-DC / 200W

20 ☐

Dimtype: non-dimmable


Cutout dimension (mm): 40

Light altering devices




19810 0010 B HONEYCOMB 42 SINGLE USE B

☐




19810 0020 LINEAR SPREAD LENS 42

☐




19810 0030 SPREAD LENS 42

☐




19810 0040 SOFTENING LENS 42

☐



19810 0050 GLASS SBL 42


☐



19810 0060 B HONEYCOMB 42 DOUBLE USE B

☐

Finish your product



19810 0100 B SPY 52 TUBE B

☐

19810 0100 FBR SPY 52 TUBE FBR

☐

DELTALIGHT

SUPERLOOP-SPY 52 93045 MDL




20567 9330 FG

19810 0100 FG	SPY 52 TUBE FG	☐
19810 0100 GC	SPY 52 TUBE GC	☐
19810 0100 W	SPY 52 TUBE W	☐

Replaceable reflector / lens

	19810 0180 SPY 52 REFLECTOR 20°	☐
	19810 0190 SPY 52 REFLECTOR 45°	☐
	19810 0240 SPY 52 REFLECTOR 30°	☐


COMPATIBLE COMPOSABLES

SUPERLOOP HC MDL	Available Colours
 418 481 07 SUPERLOOP HC 70 MDL	  
 418 481 09 SUPERLOOP HC 90 MDL	  
 418 481 12 SUPERLOOP HC 120 MDL	  

DELTALIGHT

SUPERLOOP-SPY 52 93045 MDL

20567 9330 FG




418 481 17

SUPERLOOP HC 170 MDL



SUPERLOOP HC MDL XL


Available Colours



20555 0000

SUPERLOOP HC 200 MDL






20556 0000

SUPERLOOP HC 250 MDL






20557 0000

SUPERLOOP HC 300 MDL






20558 0000

SUPERLOOP HC 350 MDL






20559 0000

SUPERLOOP HC 400 MDL






20560 0000

SUPERLOOP HC 500 MDL



SUPERLOOP PLUS MDL


Available Colours



20564 0000

SUPERLOOP PLUS HC 70 MDL





20565 0000


SUPERLOOP PLUS HC 90 MDL



DELTALIGHT

SUPERLOOP-SPY 52 93045 MDL

20567 9330 FG




20566 0000

SUPERLOOP PLUS HC 120 MDL



SUPERLOOP S HC MDL


Available Colours



418 482 106

SUPERLOOP S HC 106 MDL






418 482 109

SUPERLOOP S HC 109 MDL






418 482 211

SUPERLOOP S HC 211 MDL





418 482 217

SUPERLOOP S HC 217 MDL



Notes: