



OML50 - PRISMATIC LENS DU HE 1640mm 940 DIM5

31642 9405 B

BESCHIKBAAR IN
ZWART 31642 9405 B



[Bekijk op website](#)



Algemene info

| | |
|-------------------------------|--|
| LOCATIE | binnen |
| STOF EN WATERDICHTHEID | IP20 |
| GEWICHT (KG) | 2.4 |
| INFO | INCL.DIMMABLE LED POWER SUPPLY (DALI-2 standard) CABLING 1 CIRCUIT |

Elektrische info

| | |
|---------------------------|----------------------|
| ELEKTRISCH | 220-240V / 0 50-60Hz |
| KLASSE | I |
| VOEDING INBEGREPEN | YES |
| DIM TYPE | DALI |
| ENERGIE KLASSE | D |
| CERTIFICATES | EPD, RCM |

Info lichtbron

| | |
|---------------------------------|--|
| LIGHTSOURCE NAME | LED |
| LICHTBRON | DOWN: LED cluster 24,4W / CRI>90 (R9: 50) / 4000K / 4158lm UP: LED cluster 20,4W / CRI>90 (R9: 50) / 4000K / 3304lm |
| TM-30 WAARDEN | Rf: 90 / Rg: 101 |
| SMDC | SDCM3 |
| RISK-GROEP | RG1 |
| LM80 | L80 > 60000 |
| LED TECHNIEK (LICHTBRON) | DOWN: 4158lm // 24,4W // 171lm/W UP: 3304lm // 20,4W // 162lm/W |

Opties

WIRELESS CONTROL DIM5

Notes: