



## BOXY L+ 93033 DIM8



251 67 811 932 ED8 B-B

AVAILABLE IN

**ALU GREY-ALU GREY** 251 67 811 932 ED8 A-A

**BLACK-BLACK** 251 67 811 932 ED8 B-B

**WHITE-WHITE** 251 67 811 932 ED8 W-W



[View on website](#)



| General info                         |                                                         |
|--------------------------------------|---------------------------------------------------------|
| LOCATION                             | indoor-outdoor                                          |
| INSTALLATION                         | Ceiling Surface mounted                                 |
| INGRESS PROTECTION                   | IP53                                                    |
| PROTECTION AGAINST MECHANICAL IMPACT | IK03                                                    |
| WEIGHT (KG)                          | 0.5                                                     |
| ADJUSTABILITY                        | non adjustable                                          |
| INFORMATION                          | REFLECTOR FL-33°<br>INCL.DIMMABLE POWER SUPPLY 350mA-DC |
| Electrical info                      |                                                         |
| ELECTRICAL                           | 220-240V / 50-60Hz                                      |
| CLASS                                | II                                                      |
| POWER SUPPLY                         | YES                                                     |
| DIM TYPE                             | mains (phase cut-off)                                   |
| ENERGY CLASS                         | C                                                       |
| CERTIFICATES                         | CB, EAC, ENEC, LCA, RCM                                 |
| Lightsource info                     |                                                         |
| LIGHTSOURCE NAME                     | LED                                                     |
| LIGHTSOURCE                          | LED array 5,8W / CRI>90 (R9: 52) / 3000K / 787lm        |
| TM-30 VALUES                         | rf: 90 / Rg: 99                                         |
| SDCM                                 | SDCM1                                                   |
| RISKGROUP                            | RG1                                                     |
| LM80                                 | L90B10 > 50000                                          |
| BEAMANGLE                            | 33°                                                     |
| LED TECHNICS (LIGHT SOURCE)          | 787lm // 5,8W // 135lm/W                                |
| LED TECHNICS (LUMINAIRE)             | 628lm // 6,7W // 94lm/W                                 |

For detailed installation instructions, please consult the manual : [251\\_67\\_811\\_XXX\\_ED8\\_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Miscellaneous control equipment



**300 90 004 ED8** WIRELESS CONTROL DIM8

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 40

☐

Light altering devices



**251 70 03 01 B** BOXY HONEYCOMB B

☐

**251 70 03 01 W** BOXY HONEYCOMB W

☐

**251 70 03 04 B** BOXY SOFTENING LENS B

☐

**251 70 03 04 W** BOXY SOFTENING LENS W

☐

**251 70 03 05 B** BOXY GLASS SBL B

☐

**251 70 03 05 W** BOXY GLASS SBL W

☐

Notes: