
DELTALIGHT




COMPO M IP44 94020

REFERENCE 9 15751 9420 C

AVAILABLE IN
BLACK 9 15751 9420 B
CHROMED 9 15751 9420 C
DARK CHROMED 9 15751 9420 DC
WHITE 9 15751 9420 W





View on website

General info	
LOCATION	indoor-outdoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 110
RECESSED DEPTH (MM)	105
THICKNESS OF MOUNTING SURFACE (MM)	max.25
INGRESS PROTECTION	IP44/20
WEIGHT (KG)	0.27
ADJUSTABILITY	0° to 30° swiveling, 355° rotatable

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	F

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 12,5W / CRI>90 (R9: 79) / 4000K / 1457lm
TM-30 VALUES	Rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	20°
LED TECHNICS (LIGHT SOURCE)	1457lm // 12,5W // 117lm/W
LED TECHNICS (LUMINAIRE)	836lm // 14,4W // 58lm/W

Requirements

LED POWER SUPPLY 700 mA - DC

Accessories

COMPO M HONEYCOMB SINGLE USE B
COMPO M LINEAR SPREAD LENS
COMPO M SPREAD LENS
COMPO M SOFTENING LENS
COMPO M GLASS SBL

For detailed installation instructions, please consult the manual : **9_15751_XXX0_HAND.pdf**

COMPO M IP44 94020

9 15751 9420 C

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
 **System ceiling**	15710 0020 - MOUNTING KIT COMPO M TRIM	Required
	15710 0050 - MOUNTING KIT COMPO M TRIMLESS	Required
 **Plasterboard**	15710 0020 - MOUNTING KIT COMPO M TRIM	Required
	15710 0050 - MOUNTING KIT COMPO M TRIMLESS	Required
 **Wood**	15710 0020 - MOUNTING KIT COMPO M TRIM	Required
	15710 0050 - MOUNTING KIT COMPO M TRIMLESS	Required

FINISH YOUR SPECIFICATION

LED Power supply

of Fixtures

Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


15710 3100	LED POWER SUPPLY 18W NO DIM 1400mA	1->4 ☐
15710 3500	LED POWER SUPPLY MULTIPOWER 15W NO DIM 700mA	1 ☐
15710 4000	LED POWER SUPPLY MULTIPOWER 15W DIM8 700mA	1 ☐
15710 4900	LED POWER SUPPLY MULTIPOWER 20W DIM1 700mA	1 ☐
15710 5000	LED POWER SUPPLY MULTIPOWER 55W DALI DT6 1400mA	1->13 ☐

Dimtype: DALI

15710 5600	LED POWER SUPPLY MULTIPOWER 20W DALI DT6 700mA	1 ☐

Dimtype: DALI

Mounting kits



15710 0020 B MOUNTING KIT COMPO M TRIM B ☐

Cutout dimension (mm): 76

15710 0020 W MOUNTING KIT COMPO M TRIM W ☐

DELTALIGHT

COMPO M IP44 94020

9 15751 9420 C



15710 0050 MOUNTING KIT COMPO M TRIMLESS

Cutout dimension (mm): 76

Light altering devices

15710 1100 B COMPO M HONEYCOMB SINGLE USE B

15710 1110 COMPO M LINEAR SPREAD LENS

Cutout dimension (mm): 32,5

15710 1120 COMPO M SPREAD LENS

Cutout dimension (mm): 32,5

15710 1130 COMPO M SOFTENING LENS

Cutout dimension (mm): 32,5

15710 1140 COMPO M GLASS SBL

Cutout dimension (mm): 32,5

Notes: