



## LOGIC LINEAR 880 92725

30820 9220 INOX

AVAILABLE IN  
**INOX** 30820 9220 INOX



 [View on website](#)



### General info

<b>LOCATION</b>	outdoor
<b>INSTALLATION</b>	Floor Recessed
<b>CUTOUT SHAPE/SIZE (MM)</b>	rectangle - BOX
<b>RECESSED DEPTH (MM)</b>	140
<b>INGRESS PROTECTION</b>	IP67
<b>PROTECTION AGAINST MECHANICAL IMPACT</b>	IK09
<b>WEIGHT (KG)</b>	4.4
<b>ADJUSTABILITY</b>	non adjustable
<b>INFORMATION</b>	16 x LENS FL-25° INCL.LED POWER SUPPLY 650mA-DC INCL.1 x CABLE H05 RN-F 3 x 0.75mm <sup>2</sup> 0,5m INCL.IP68 CONNECTOR 3P ESG 8mm max.500kg

### Electrical info

<b>ELECTRICAL</b>	220-240V / 0 50-60Hz
<b>CLASS</b>	I
<b>POWER SUPPLY</b>	YES
<b>DIM TYPE</b>	non-dimmable
<b>ENERGY CLASS</b>	F
<b>CERTIFICATES</b>	CB, ENEC, EPD, RCM

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	LED cluster 28,8W / CRI>90 (R9: 55) / 2700K / 3288lm
<b>TM-30 VALUES</b>	Rf: 91 / Rg: 100
<b>SDCM</b>	SDCM3
<b>RISKGROUP</b>	RG2
<b>LM80</b>	L80 > 150000
<b>BEAMANGLE</b>	25°
<b>LED TECHNICS (LIGHT SOURCE)</b>	3288lm // 28,8W // 111lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	2325lm // 33,1W // 70lm/W

### Requirements


LOGIC LINEAR BOX

For detailed installation instructions, please consult the manual : [30820\\_XXX0\\_HAND.pdf](#)

### FINISH YOUR SPECIFICATION

#### Ground mounting boxes

---



**30810 0030** LOGIC LINEAR 880 BOX


Cutout dimension (mm): 920 x 150

#### Waterproof connection parts

---



**431 99 02** IP68 JUNCTION BOX 4P



**21034 0150** IP68 Y-CONNECTOR 5P

Notes: