
DELTALIGHT




COMPO S 93041

REFERENCE 9 15711 9330 C

AVAILABLE IN
BLACK 9 15711 9330 B
CHROMED 9 15711 9330 C
DARK CHROMED 9 15711 9330 DC
WHITE 9 15711 9330 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 90
RECESSED DEPTH (MM)	85
THICKNESS OF MOUNTING SURFACE (MM)	max.25
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.124
ADJUSTABILITY	0° to 30° swiveling, 355° rotatable

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	F

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 6,4W / CRI>90 / 3000K / 664lm
BEAMANGLE	40°
LED TECHNICS (LIGHT SOURCE)	664lm // 6,4W // 120lm/W
LED TECHNICS (LUMINAIRE)	504lm // 7,4W // 68lm/W

Requirements

LED POWER SUPPLY 350 mA - DC

Accessories

COMPO S HONEYCOMB SINGLE USE B
COMPO S LINEAR SPREAD LENS
COMPO S SPREAD LENS
COMPO S SOFTENING LENS
COMPO S GLASS SBL

For detailed installation instructions, please consult the manual : **9_15711_XXX0_HAND.pdf**

DELTALIGHT

COMPO S 93041

9 15711 9330 C

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
 **System ceiling**	15710 0010 - MOUNTING KIT COMPO S TRIM	Required
	15710 0040 - MOUNTING KIT COMPO S TRIMLESS	Required
 **Plasterboard**	15710 0010 - MOUNTING KIT COMPO S TRIM	Required
	15710 0040 - MOUNTING KIT COMPO S TRIMLESS	Required
 **Wood**	15710 0010 - MOUNTING KIT COMPO S TRIM	Required
	15710 0040 - MOUNTING KIT COMPO S TRIMLESS	Required

FINISH YOUR SPECIFICATION

LED Power supply

of Fixtures

of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current

15710 3100	LED POWER SUPPLY 18W NO DIM 1400mA	1->4
15710 3300	LED POWER SUPPLY MULTIPOWER 15W NO DIM 350mA	1->2
15710 3800	LED POWER SUPPLY MULTIPOWER 10W DIM8 350mA	1
15710 4500	LED POWER SUPPLY MULTIPOWER 12W DIM1 350mA	1
15710 5000	LED POWER SUPPLY MULTIPOWER 55W DALI DT6 1400mA	1->13

Dimtype: DALI

15710 5300	LED POWER SUPPLY MULTIPOWER 12W DALI DT6 350mA	1

Dimtype: DALI

Mounting kits



15710 0010 B MOUNTING KIT COMPO S TRIM B

Cutout dimension (mm): 55

15710 0010 W MOUNTING KIT COMPO S TRIM W

DELTALIGHT

COMPO S 93041

9 15711 9330 C



15710 0040 MOUNTING KIT COMPO S TRIMLESS

Cutout dimension (mm): 55

Light altering devices

15710 0100 B COMPO S HONEYCOMB SINGLE USE B

15710 0110 COMPO S LINEAR SPREAD LENS

Cutout dimension (mm): 26,5

15710 0120 COMPO S SPREAD LENS

Cutout dimension (mm): 26,5

15710 0130 COMPO S SOFTENING LENS

Cutout dimension (mm): 26,5

15710 0140 COMPO S GLASS SBL

Cutout dimension (mm): 26,5

Notes: