
DELTALIGHT




DEEP RINGO HE 93040

REFERENCE 19440 9330 BROB

AVAILABLE IN
NOIR 19440 9330 B
ALU BROSSÉ 19440 9330 BRA
ANTHRACITE BROSSÉ 19440 9330 BRAT
BRONZE BRUN BROSSÉ 19440 9330 BRBB
CUIVRE BROSSÉ 19440 9330 BRCU
OR BROSSÉ 19440 9330 BRG
BRONZE VIEUX BROSSÉ 19440 9330 BROB
CRÈME 19440 9330 CR
FLEMISH BRONZE 19440 9330 FBR
FLEMISH GOLD 19440 9330 FG
COULEUR OR 19440 9330 GC
NOIR PIANO 19440 9330 PB
BLANC 19440 9330 W





View on website

General info	
LOCATION	interieur
INSTALLATION	Plafond Encastré
CUTOUT SHAPE/SIZE (MM)	circulaire - 76
RECESSED DEPTH (MM)	90
THICKNESS OF MOUNTING SURFACE (MM)	min.5
INGRESS PROTECTION	IP43/20
WEIGHT (KG)	0.2
ADJUSTABILITY	non réglable
INFORMATION	LENS WFL-40° EXCL.LED POWER SUPPLY 350mA-DC

Electrical info	
CLASS	III
DIM TYPE	selon le type d'alimentation externe
ENERGY CLASS	D
CERTIFICATION	EPD, LCA

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 6W / CRI>90 (R9: 50) / 3000K / 945lm
SDMC	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	40°
LED TECHNICS (LIGHT SOURCE)	945lm // 6W // 157lm/W
LED TECHNICS (LUMINAIRE)	768lm // 7W // 111lm/W

Remarks

High Efficacy : > 100lm/W

Requirements

LED POWER SUPPLY 350mA-DC DIM

DELTALIGHT

DEEP RINGO HE 93040

19440 9330 BROB


For detailed installation instructions, please consult the manual : **19440_XXX0_HAND.pdf**

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 **System ceiling**	-
 **Plasterboard**	-
 **Stucanet**	-
 **Wood**	-
 **Concrete**	-
 **Concrete + plaster**	-
 **Lintel + plaster**	-
 **Hollow-core slab**	-
 **Hollow-core slab + plaster**	-
 **Stretched ceiling**	-

FINISH YOUR SPECIFICATION

les batteries de secours



21032 0270 B EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER B

Cutout dimension (mm): 27

21032 0270 W EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER W

DELTALIGHT

DEEP RINGO HE 93040


19440 9330 BROB

les alimentations led

of Fixtures

web2print_power_supply_info_box


Min current | Max current



300 90 91 LED POWER SUPPLY 350mA-DC / 15W 2(1)

Dimtype: non dimmable


Cutout dimension (mm): 40



300 90 110 LED POWER SUPPLY 350mA-DC / 10W DIM8 1

Dimtype: fin de phase

Cutout dimension (mm): 42



300 90 116 LED POWER SUPPLY 350mA-DC / 18W DIM8 2->2

Dimtype: fin de phase

Cutout dimension (mm): 55



21012 0515 LED POWER SUPPLY MULTI POWER DIM5 1(1)

Dimtype: DALI

Cutout dimension (mm): 55



21012 0520 LED POWER SUPPLY 350mA-DC / 8W 1(0)

Dimtype: non dimmable

Cutout dimension (mm): 47



21012 0575 LED POWER SUPPLY MULTI POWER DIM5 2->3(2)

Dimtype: DALI

Cutout dimension (mm): 55

Notes: