
DELTALIGHT




OONO W S 927 DIM8

REFERENCE 29611 9208 W

AVAILABLE IN
ALU GREY 29611 9208 A
BLACK 29611 9208 B
FLEMISH BRONZE OUTDOOR 29611 9208 FBRX
GOLD MARBLED 29611 9208 GM
ANTHRACITE 29611 9208 N
WHITE 29611 9208 W





View on website

General info	
LOCATION	indoor-outdoor
INSTALLATION	Wall Surface mounted
INGRESS PROTECTION	IP54
PROTECTION AGAINST MECHANICAL IMPACT	IK04
WEIGHT (KG)	1.1
ADJUSTABILITY	non adjustable
INFORMATION	INCL.DIMMABLE LED POWER SUPPLY 500mA-DC GM (Gold Marbled) version only for interior use

Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	E

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 60) / 2700K / 1041lm
TM-30 VALUES	Rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1041lm // 8,6W // 121lm/W
LED TECHNICS (LUMINAIRE)	572lm // 9,9W // 58lm/W

For detailed installation instructions, please consult the manual : **29611_XXX8_HAND.pdf**

Notes:

OONO W S 927 DIM8

29611 9208 W