





SUPERLOOP-FIX 40 DOWN-UP 82720 MDL

REFERENCE

418 162 822 MDL B

AVAILABLE IN

BLACK 418 162 822 MDL B



[View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.2
ADJUSTABILITY	non adjustable
INFORMATION	DOWN : LENS FL-20° INCL.CLIP 48V ADAPTER EXCL.LED POWER SUPPLY 48V-DC
Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1-10V or DALI or push button
ENERGY CLASS	E
CERTIFICATES	CB, EAC, ENEC
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN: LED array 4,1W / CRI>80 / 2700K / 420lm UP: 2,1W / CRI>80 / 2700K / 213lm
SDCM	SDCM2
BEAMANGLE	20°
LED TECHNICS (LIGHT SOURCE)	DOWN: 420lm // 4,1W // 103lm/W UP: 213lm // 2,1W // 101lm/W
LED TECHNICS (LUMINAIRE)	DOWN: 328lm // 4,7W // 70lm/W UP: 153lm // 2,4W // 64lm/W
Requirements	
LED POWER SUPPLY 48V-DC	
Options	
DIMMABLE MODULATOR	

For detailed installation instructions, please consult the manual : [418_162_8XX_MDL_HAND.pdf](#)

SUPERLOOP-FIX 40 DOWN-UP 82720 MDL

418 162 822 MDL B

FINISH YOUR SPECIFICATION


SMART 48

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



300 90 011 SMART 48 MODULATOR DIM9

26

Dimtype: 1-10V or DALI or push button



300 90 012 SMART 48 MODULATOR WD

26

Dimtype: WDL = wireless dimmable


LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




300 89 48 90 LED POWER SUPPLY 48V-DC / 90W

12

Dimtype: non-dimmable


Cutout dimension (mm): 75



300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN

14


Dimtype: non-dimmable



300 89 48 150 LED POWER SUPPLY 48V-DC / 150W

21

Dimtype: non-dimmable



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN



33

Dimtype: non-dimmable







DELTALIGHT

SUPERLOOP-FIX 40 DOWN-UP 82720 MDL

418 162 822 MDL B

	21012 0230 LED POWER SUPPLY 48V-DC / 100W	14 ☐
Dimtype: non-dimmable		
Cutout dimension (mm): 40		
	21012 0240 LED POWER SUPPLY 48V-DC / 200W	28 ☐
Dimtype: non-dimmable		
Cutout dimension (mm): 40		





COMPATIBLE COMPOSABLES





SUPERLOOP HC MDL	Available Colours
	
	
	
	
SUPERLOOP HC MDL XL	Available Colours
	
	

DELTALIGHT

SUPERLOOP-FIX 40 DOWN-UP 82720 MDL

418 162 822 MDL B

	20557 0000 SUPERLOOP HC 300 MDL	
	20558 0000 SUPERLOOP HC 350 MDL	
	20559 0000 SUPERLOOP HC 400 MDL	
	20560 0000 SUPERLOOP HC 500 MDL	

SUPERLOOP S HC MDL		Available Colours
	418 482 106 SUPERLOOP S HC 106 MDL	
	418 482 109 SUPERLOOP S HC 109 MDL	
	418 482 211 SUPERLOOP S HC 211 MDL	
	418 482 217 SUPERLOOP S HC 217 MDL	

Notes: