
DELTALIGHT




KIX II PIN 93055

REFERENCE 13537 9330 N

AVAILABLE IN
ALU GREY 13537 9330 A
ANTHRACITE 13537 9330 N
PINE GREEN 13537 9330 PGR





View on website

General info	
LOCATION	outdoor
INSTALLATION	Floor Surface mounted
INGRESS PROTECTION	IP65
PROTECTION AGAINST MECHANICAL IMPACT	IK03
WEIGHT (KG)	1.2
ADJUSTABILITY	180° swiveling, 360° rotatable
INFORMATION	REFLECTOR WFL-55° INCL.1 x CABLE H05 RN-F 2 x 1mm² 2m INCL.LED POWER SUPPLY 350mA-DC

Electrical info	
ELECTRICAL	100-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	C

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8W / CRI>90 (R9: 52) / 3000K / 787lm
TM-30 VALUES	Rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	55°
LED TECHNICS (LIGHT SOURCE)	787lm // 5,8W // 135lm/W
LED TECHNICS (LUMINAIRE)	646lm // 6,7W // 97lm/W

Options

CBOX
IP68 CONNECTION KIT
IP68 CONNECTOR 3P

Accessories

KAP KIX
HONEYCOMB KIX

DELTALIGHT


KIX II PIN 93055

13537 9330 N

For detailed installation instructions, please consult the manual : **13537_XXX0_HAND.pdf**

FINISH YOUR SPECIFICATION


Waterproof connection parts



216 12 00 CBOX

Cutout dimension (mm): 142 x 142

☐



216 12 01 IP68 CONNECTION KIT


☐



216 12 02 IP68 CONNECTOR 3P


☐

Light altering devices



232 10 00 N KAP KIX N

☐



232 10 03 N HONEYCOMB KIX N

☐

Notes: