
DELTALIGHT




SOLI - FORM 110 DOWN-UP 2 CIRCUIT 93067 Q-DIM

REFERENCE 27148 932Q W-W

AVAILABLE IN
BLACK-BLACK 27148 932Q B-B
BLACK-FLEMISH GOLD 27148 932Q B-FG
WHITE-BLACK 27148 932Q W-B
WHITE-WHITE 27148 932Q W-W





View on website

General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.9
ADJUSTABILITY	non adjustable
INFORMATION	INCL.48 x REFLECTOR FL-67° EXCL.LED POWER SUPPLY 48V-DC 2 CIRCUITS

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	Qbus dim
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, LCA

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN: LED cluster 14,1W / CRI>90 (R9: 50) / 3000K / 2136lm UP: LED cluster 14,1W / CRI>90 (R9: 50) / 3000K / 2136lm
TM-30 VALUES	Rf: 92 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
BEAMANGLE	67°
LED TECHNICS (LIGHT SOURCE)	DOWN: 2136lm // 14,1W // 152lm/W UP: 2136lm // 14,1W // 152lm/W
LED TECHNICS (LUMINAIRE)	DOWN: 1816lm // 16W // 112lm/W UP: 1431lm // 16W // 88lm/W

Requirements

LED POWER SUPPLY 48V-DC

For detailed installation instructions, please consult the manual : **27148_XXXQ_HAND.pdf**

DELTALIGHT

SOLI - FORM 110 DOWN-UP 2 CIRCUIT 93067 Q-DIM

27148 932Q W-W


FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures


of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN — 3

Dimtype: non-dimmable



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN — 7


Dimtype: non-dimmable



21012 0230 LED POWER SUPPLY 48V-DC / 100W — 3

Dimtype: non-dimmable

Cutout dimension (mm): 40



21012 0240 LED POWER SUPPLY 48V-DC / 200W — 6


Dimtype: non-dimmable

Cutout dimension (mm): 40


COMPATIBLE COMPOSABLES

SOLISCAPE profile

Available Colours



27111 0020 SOLI - PROFILE 2m



27111 0030 SOLI - PROFILE 3m

Notes:

SOLI - FORM 110 DOWN-UP 2 CIRCUIT 93067 Q-DIM

27148 932Q W-W