




FRAX S SUPERSPOT 92708

REFERENCE 26101 9210 N

AVAILABLE IN
ALU GREY 26101 9210 A
FLEMISH BRONZE OUTDOOR 26101 9210 FBRX
ANTHRACITE 26101 9210 N



 [View on website](#)




General info	
LOCATION	outdoor
INSTALLATION	Floor Surface mounted,Wall Surface mounted
INGRESS PROTECTION	IP65
PROTECTION AGAINST MECHANICAL IMPACT	IK06
WEIGHT (KG)	1.5
ADJUSTABILITY	0° to 120° swiveling, 360° rotatable
INFORMATION	3 x LENS SP-8° INCLLED POWER SUPPLY 700mA-DC
Electrical info	
ELECTRICAL	100-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	F
CERTIFICATES	CB, EPD, RCM
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 6W / CRI>90 (R9: 55) / 2700K / 659lm
TM-30 VALUES	Rf: 91 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 150000
BEAMANGLE	8°
LED TECHNICS (LIGHT SOURCE)	659lm // 6W // 110lm/W
LED TECHNICS (LUMINAIRE)	587lm // 6,9W // 85lm/W
Options	
FRAX ANTI VANDAL SCREWS	
Accessories	
FRAX S KAP	

For detailed installation instructions, please consult the manual : [26101_XX10_HAND.pdf](#)

FINISH YOUR SPECIFICATION


Light altering devices



26070 0010 N FRAX S KAP N

☐

Other



26070 0030 FRAX ANTI VANDAL SCREWS 5 PCS

☐

Notes: