



# MULTINOVA 255 & 355



As a disc of light, Nova refers to the Supernova range, as both families share similarities in looks and ways of installation. Offered as a down and down-up version and a limited height of only 2"-3/4", Multinova comes in our standard black or white and can also be finished in the warmer Gold Colored. To top it off – next to a opal sandblasted or prismatic optic – one can opt for a smoked sheet at the front for a more decorative touch. When turned on the disc is fully lit, when turned off a deep dark arises, ideal in combination with a Gold Colored Multinova.

Specification	
Adjustability:	Fixed
Rating:	IP20

Performance	Static CCT	Soft Dim
CRI:	90	90
*Multinova 2R SP:	2 x 34.4W	2 x 32.3W
*Multinova 3R SP:	3 x 34.4W	3 x 32.3W

Delivered Lumens	3000K	2700-1800K
Multinova 2R Opal:	7683Lm	7361Lm
Multinova 2R Prism:	6932Lm	
Multinova 2R Smoke:	4606Lm	
Multinova 3R Opal:	11525Lm	11042Lm
Multinova 3R Prism:	10398Lm	
Multinova 3R Smoke:	6909Lm	

#### Listing

ETL certified to US and Canadian safety standards.

#### Warranty

5-year limited warranty.

## Ordering

ALL BOXES MUST BE FILLED IN TO CORRECTLY ORDER

Example: MNV3R05F-PCPRBD14-120INC-SPDN30-GC-S

Luminaire	Shape	Size	Function	Style	Installation	Hardware Finish <sup>(2)</sup>	Controls	Application	Downlight	Uplight	CCT	Finish	Lens
MNV MULTINOVA	2R 2 X Round (Multinova 255)	05 550mm / 21 <sup>21</sup> / <sub>32</sub> "	F Fixed	PC <sup>(1)</sup> Pendant, cable suspended	PR Round coverplate for 4" junction box	B Black  W White	D14-120 FE ELV dim 120V / 0-10V dim 120/277V	INC Integral Power Supply	SP Standard Power	DN Downlight only, no uplight	30 3000K  SD 3000- 1800K	B Black  GC <sup>(3)</sup> Gold Colored  W White	O Opal  P <sup>(3,4)</sup> Prismatic  S <sup>(4)</sup> Smoke

<sup>1</sup> Shape 2R has 2 suspension points; Shape 3R has 3 suspension points.

<sup>2</sup> Applies to PR (coverplate).

<sup>3</sup> Finish GC not offered with Lens Option P.


<sup>4</sup> Not offered with Soft Dim.

## Related Products

Supernova, Supernova XS, Supernova XS ADM (track), Multinova 30/55, M-Multinova

## Finish Options


### LENS





## Finish Options (cont'd)

### MULTINOVA 2R



BLACK




WHITE



GOLD COLORED

### MULTINOVA 3R



BLACK




WHITE



GOLD COLORED

## Installation Options


### PR - COVERPLATE R 212



BLACK or WHITE  
Requires 4" junction box

## Photometric Data

### MULTINOVA R05



## Driver Options

### D14

- Dimming Control Phase Control or -10V
- Dimming Range 1-100%
- Dim to off yes
- Power Factor @ Full Load >0.9
- Efficiency @ Full Load ≥90
- THD @ Full Load <20%

#### Dimmer Compatibility Phase

- Leviton IP1106-1LZ / 6631-2
- Leviton DVELV-303P / MAELV-600

#### Dimmer Compatibility 0-10V

- Leviton IP710-DLZ
- Leviton DVTX-XX

As technology changes, please use information above as guidance. For most recent updated information please contact factory. Specifications subject to change without notice.