MULTINOVA 255 & 355



As a disc of light, Nova refers to the Supernova range, as both families share similarities in looks and ways of installation. With the single units offered in two diameters as a down or down-up with a limited height of only 2"-3/4, Multinova comes in our standard black, white, and gold colored. To top it off, next to an opal sandblasted lens or prismatic optic, the pendant version is available in single, double, or triple pendant options, making it suitable for use in small and larger rooms that require a larger lighting solution.

Specification	
Adjustability:	Fixed
Rating:	Damp

Performance	Fixed CCT	Soft Dim
CRI / TM-30 (3000K):	90 / Rf: 89 / Rg: 97	90 / Rf: 89 / Rg: 99
SDCM:	3	3
LED Maintenance:	L70>60,000h	L70>60,000
*Standard Power Shape 2R:	2 x 39.6W	2 x 37.1W
*Standard Power Shape 3R:	3 x 39.6W	3 x 37.1W

Delivered Lumens	3000K	2700-1800K
Shape 2R Lens Opal:	7683	7361
Shape 2R Lens Prismatic:	6932	
Shape 3R Lens Opal:	11525	11042
Shape 3R Lens Prismatic:	10398	

Listing
ETL certified to US and Canadian safety standards.

Warranty
5-year limited warranty.

Ordering
ALL BOXES MUST BE FILLED IN TO CORRECTLY ORDER

Example: MNV3R05F-PCPRBD14-120INC-SPDNSD-GC-O

Luminaire	Shape	Size	Function	Style	Installation	Hardware Finish[2]	Controls	Application	Downlight	Uplight	CCT	Finish	Lens
MNV MULTINOVA	**2R** 2 X Round (Multinova 255) **3R** 3 X Round (Multinova 255)	**05** 550mm / 21 21/32"	**F** Fixed	**PC**[1] Pendant, cable suspended	**PR** Round coverplate for 4" junction box	**B** Black **W** White	**D14-120** FE ELV dim 120V / 0-10V dim 120-277V	**INC** Integral Power Supply	**SP** Standard Power	**DN** Downlight only, no uplight	**30** 3000K	**B** Black **W** White	**O** Opal **P** Prismatic
												GC Gold Colored	**O** Opal
											SD Soft Dim 3000-1800K	**B** Black **GC** Gold Colored **W** White	


1 Shape 2R has 2 suspension points; Shape 3R has 3 suspension points.
2 Applies to PR (coverplate).

Related Products

Supernova, Multinova 30/55, M-Multinova

Finish Options


LENS


OPAL


PRISMATIC
(UGR<19)

Finish Options (cont.)

MULTINOVA 2R





BLACK


WHITE


GOLD COLORED

MULTINOVA 3R





BLACK


WHITE


GOLD COLORED

Installation Options


PR - COVERPLATE R 212



BLACK OR WHITE
Requires 4" junction box

Photometric Data

MULTINOVA R05



Driver Options

D14

- Dimming Control: Phase Control or -10V
- Dimming Range: 1-100%
- Dim to off: yes
- Power Factor @ Full Load: >0.9
- Efficiency @ Full Load: ≥90
- THD @ Full Load: <20%

Dimmer Compatibility Phase

- Leviton IP1106-1LZ / 6631-2
- Leviton DVELV-303P / MAELV-600

Dimmer Compatibility 0-10V

- Leviton IP710-DLZ
- Leviton DVTV-XX

As technology changes, please use information above as guidance. For most recent updated information please contact factory. Specifications subject to change without notice.

DELTALIGHT