DELTALIGHT



OML50 - PRISMATIC LENS DU HE 1968mm 930 DIM5

REFERENCE 31643 9305 B

AVAILABLE IN
BLACK 31643 9305 B

View on website

General info	
LOCATION	indoor
INGRESS PROTECTION	IP20
WEIGHT (KG)	2.8
INFORMATION	INCL.DIMMABLE LED POWER SUPPLY (DALI-2 standard) CABLING 1 CIRCUIT

Electrical info	
ELECTRICAL	220-240V / 0|50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	D
CERTIFICATES	EPD, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN: LED cluster 29,2W / CRI>90 (R9: 50) / 3000K / 4788lm UP: LED cluster 24,5W / CRI>90 (R9: 50) / 3000K / 3802lm
TM-30 VALUES	Rf: 92 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	DOWN: 4788lm // 29,2W // 164lm/W UP: 3802lm // 24,5W // 155lm/W

Options

WIRELESS CONTROL DIM5

Notes:

Delta Light NV may revise the information and technical data at any time without notice. Version: 08/10/2026