



OML50 - PRISMATIC LENS DU HE 1968mm 930 DIM5

31643 9305 B

BESCHIKBAAR IN
ZWART 31643 9305 B



[Bekijk op website](#)



Algemene info

LOCATIE	binnen
STOF EN WATERDICHTHEID	IP20
GEWICHT (KG)	2.8
INFO	INCL.DIMMABLE LED POWER SUPPLY (DALI-2 standard) CABLING 1 CIRCUIT

Elektrische info

ELEKTRISCH	220-240V / 0 50-60Hz
KLASSE	I
VOEDING INBEGREPEN	YES
DIM TYPE	DALI
ENERGIE KLASSE	D
CERTIFICATES	EPD, RCM

Info lichtbron

LIGHTSOURCE NAME	LED
LICHTBRON	DOWN: LED cluster 29,2W / CRI>90 (R9: 50) / 3000K / 4788lm UP: LED cluster 24,5W / CRI>90 (R9: 50) / 3000K / 3802lm
TM-30 WAARDEN	Rf: 92 / Rg: 100
SMD	SDCM3
RISK-GROEP	RG1
LM80	L80 > 60000
LED TECHNIEK (LICHTBRON)	DOWN: 4788lm // 29,2W // 164lm/W UP: 3802lm // 24,5W // 155lm/W

Opties

WIRELESS CONTROL DIM5

Notes: