


27327 9200 FBR

Technical drawing of a mechanical part, likely a bracket or support. The drawing shows a side view of a component with a cylindrical feature. Dimensions are indicated: 160 (total length), 7 (thickness), 20 (width of a step), 11 (height of a base), 92 (length of the main body), and Ø39 (diameter of the cylinder). A circular feature is shown with a dimension of 0.85° ± 5°.



Options
DIMMABLE MODULATOR

1 / 3


FINISH YOUR SPECIFICATION

SMART 48

of Fixtures

 web2print_power_supply_info_box

Min current | Max current




300 90 011

SMART 48 MODULATOR DIM9

19

Dimtype: 1 à 10 V ou DALI ou bouton poussoir



300 90 012

SMART 48 MODULATOR WD

19


Dimtype: WDL = dimmable sans fil

les alimentations led

of Fixtures

 web2print_power_supply_info_box

Min current | Max current




300 89 48 100

LED POWER SUPPLY 48V-DC / 100W DIN

10

Dimtype: non dimmable




300 89 48 240

LED POWER SUPPLY 48V-DC / 240W DIN

24

Dimtype: non dimmable




21012 0230

LED POWER SUPPLY 48V-DC / 100W

10

Dimtype: non dimmable

Cutout dimension (mm): 40



21012 0240

LED POWER SUPPLY 48V-DC / 200W

20

Dimtype: non dimmable

Cutout dimension (mm): 40

DELTALIGHT

SPL14 - SPY 39 FOCUS 927 MDL

27327 9200 FBR

COMPATIBLE COMPOSABLES

SPLITLINE 14 profile		Available Colours
	27300 0020 SPL14 - PROFILE 2m	
	27300 0030 SPL14 - PROFILE 3m	

Notes: