
DELTALIGHT




M20/M26H - SPY 391 SOFT 93040 MDL

REFERENCE 23423 9030 B

AVAILABLE IN
BLACK 23423 9030 B
BRUSHED ALU 23423 9030 BRA
BRUSHED ANTHRACITE 23423 9030 BRAT
BRUSHED COPPER 23423 9030 BRCU
BRUSHED GOLD 23423 9030 BRG
BRUSHED OLD BRONZE 23423 9030 BROB
FLEMISH BRONZE 23423 9030 FBR
FLEMISH GOLD 23423 9030 FG
GOLD COLOURED 23423 9030 GC
PIANO BLACK 23423 9030 PB
WHITE 23423 9030 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° to 85° swiveling, 355° rotatable
INFORMATION	REFLECTOR WFL-40° EXCL.LED POWER SUPPLY 48V-DC

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1-10V or DALI or push button
ENERGY CLASS	F
CERTIFICATES	EPD

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 6W / CRI>90 (R9: 50) / 3000K-1800K / 623lm
TM-30 VALUES	Rf: 90 / Rg: 99
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	40°
LED TECHNICS (LIGHT SOURCE)	623lm // 6W // 105lm/W
LED TECHNICS (LUMINAIRE)	505lm // 6,9W // 73lm/W

Requirements

SPY 39 TUBE
LED POWER SUPPLY 48V-DC

Options

DIMMABLE MODULATOR

M20/M26H - SPY 391 SOFT 93040 MDL

23423 9030 B

For detailed installation instructions, please consult the manual : **23423_XXX0_HAND.pdf**


FINISH YOUR SPECIFICATION

Current supply

# of Fixtures

Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.



21032 0030 SMART 48 MODULATOR PLUG-IN WD — 16


Dimtype: WDL = wireless dimmable

SMART 48

# of Fixtures


Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.



300 90 011 SMART 48 MODULATOR DIM9 — 16

Dimtype: 1-10V or DALI or push button



300 90 012 SMART 48 MODULATOR WD — 16


Dimtype: WDL = wireless dimmable

LED power supplies

# of Fixtures

Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.




300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN — 8

Dimtype: non-dimmable


M20/M26H - SPY 391 SOFT 93040 MDL

23423 9030 B



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN — 20


Dimtype: non-dimmable



21012 0230 LED POWER SUPPLY 48V-DC / 100W — 8

Dimtype: non-dimmable

Cutout dimension (mm): 40




21012 0240 LED POWER SUPPLY 48V-DC / 200W — 17

Dimtype: non-dimmable

Cutout dimension (mm): 40

Finish your product



24144 0010 B SPY 39 TUBE B

24144 0010 FBR SPY 39 TUBE FBR

24144 0010 FG SPY 39 TUBE FG

24144 0010 GC SPY 39 TUBE GC

24144 0010 W SPY 39 TUBE W




24144 0070 SPY 39 TUBE SBL

COMPATIBLE COMPOSABLES

SHIFTLINE M26H profile

Available Colours




23359 0000 SLM26H - PROFILE


DELTALIGHT

M20/M26H - SPY 391 SOFT 93040 MDL


23423 9030 B



23359 0010 SLM26H - PROFILE 1m



23359 0020 SLM26H - PROFILE 2m



23359 0030 SLM26H - PROFILE 3m

SPLITLINE M20 ST profile — Available Colours



23397 0000 SPM20 ST - PROFILE




23397 0020 SPM20 ST - PROFILE 2m




23397 0030 SPM20 ST - PROFILE 3m


SPLITLINE M20 profile — Available Colours



420 20 10 00 SPM20 - PROFILE 1m



420 20 20 00 SPM20 - PROFILE 2m




420 20 30 00 SPM20 - PROFILE 3m

DELTALIGHT

M20/M26H - SPY 391 SOFT 93040 MDL

23423 9030 B



23301 0000 SPM20 - PROFILE B

Notes: