



REO X 93033 S1

202 25 811 932 A

AVAILABLE IN



ALU GRIS 202 25 811 932 A

NOIR 202 25 811 932 B

FLEMISH BRONZE POUR L'EXTÉRIEUR 202 25 811 932 FBRX

ANTHRACITE 202 25 811 932 N

BLANC 202 25 811 932 W



[View on website](#)



General info

LOCATION	interieur-extérieur
INSTALLATION	Plafond Encastré
CUTOUT SHAPE/SIZE (MM)	circulaire - 76
RECESSED DEPTH (MM)	55
THICKNESS OF MOUNTING SURFACE (MM)	max.22
INGRESS PROTECTION	IP44/20
PROTECTION AGAINST MECHANICAL IMPACT	IK03
WEIGHT (KG)	0.2
ADJUSTABILITY	non réglable
INFORMATION	REFLECTOR FL-33° INCL.PC CLEAR EXCL.LED POWER SUPPLY 350-500mA-DC

Electrical info

CLASS	III
DIM TYPE	selon le type d'alimentation externe
ENERGY CLASS	D
CERTIFICATION	CB, EAC, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8-8,6W / CRI>90 (R9: 52) / 3000K / 787-1089lm
RVALUES	rf: 90 / Rg: 99
SDMC	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	33°
LED TECHNICS (LIGHT SOURCE)	1089lm // 8,6W // 127lm/W
LED TECHNICS (LUMINAIRE)	887lm // 9,9W // 90lm/W

Requirements

LED POWER SUPPLY 350 / 500mA-DC DIM


For detailed installation instructions, please consult the manual : [202 25 811 XXX HAND.pdf](#)

CEILING COMPATIBILITY



Ceiling Type	Mounting Kit
	System ceiling -
	Plasterboard -
	Stucanet -
	Wood -
	Stretched ceiling -

FINISH YOUR SPECIFICATION

les batteries de secours











	21032 0270 B EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER B	☐
	21032 0270 W EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER W	☐

les alimentations led

		# of Fixtures
 web2print_power_supply_info_box		Min current Max current
	300 48 350 ED1 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM1 Dimtype: 1 à 10 V Cutout dimension (mm): 30	1 ☐
	300 48 350 ED5 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5 Dimtype: DALI Cutout dimension (mm): 45	1 ☐

REO X 93033 SI


202 25 811 932 A

	300 48 350 MDL	LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W MDL	1	☐
Dimtype: non dimmable				
Cutout dimension (mm): 30				
	300 48 350 WDL	LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W WDL	1	☐
Dimtype: WDL = dimmable sans fil				
Cutout dimension (mm): 45				
	300 48 500 ED1	LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM1	1	☐
Dimtype: 1 à 10 V				
Cutout dimension (mm): 30				
	300 48 500 ED5	LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5	1	☐
Dimtype: DALI				
Cutout dimension (mm): 45				
	300 48 500 MDL	LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W MDL	1	☐
Dimtype: non dimmable				
Cutout dimension (mm): 30				
	300 48 500 WDL	LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W WDL	1	☐
Dimtype: WDL = dimmable sans fil				
Cutout dimension (mm): 45				
	300 90 61	LED POWER SUPPLY MULTI-POWER DIM6	2 2	☐
Dimtype: fin de phase ou bouton poussoir				
Cutout dimension (mm): 56				
	300 90 63	LED POWER SUPPLY MULTI-POWER DIM9	4(4) 4(4)	☐
Dimtype: 1 à 10 V ou DALI ou bouton poussoir				
Cutout dimension (mm): 82				
	300 90 64	LED POWER SUPPLY MULTI-POWER DIM7	2(1) 2(1)	☐
Dimtype: 1 à 10 V ou bouton poussoir				
Cutout dimension (mm): 72				
	300 90 67	LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9	2	☐
Dimtype: 1 à 10 V ou DALI ou bouton poussoir				

DELTALIGHT

REO X 93033 SI

202 25 811 932 A



300 90 68


LED POWER SUPPLY MULTI-POWER DIM5

2(2) | 2(1)



Dimtype: DALI

Cutout dimension (mm): 72



300 90 69


LED POWER SUPPLY MULTI-POWER HV DIM9

2->6(6) | 6(4)



Dimtype: 1 à 10 V ou DALI ou bouton poussoir

Cutout dimension (mm): 84



300 90 124


LED POWER SUPPLY MULTI-POWER DIM7

3(2) | 2(1)



Dimtype: 1 à 10 V ou bouton poussoir

Cutout dimension (mm): 55



300 90 125


LED POWER SUPPLY MULTI-POWER MINI DIM5

2(2) | 2(1)



Dimtype: DALI

Cutout dimension (mm): 55



300 90 135


LED POWER SUPPLY MULTI-POWER HV

3->3 | 2->3



Dimtype: non dimmable

Cutout dimension (mm): 90



21012 004W


LED POWER SUPPLY MULTI-POWER WDL

3(3) | 3(3)



Dimtype: WDL = dimmable sans fil

Cutout dimension (mm): 84



21012 005W


LED POWER SUPPLY MULTI-POWER COMPACT WDL

3 | 3



Dimtype: WDL = dimmable sans fil

Cutout dimension (mm): 54



21012 0258


LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8

1



Dimtype: fin de phase

Cutout dimension (mm): 50



21012 0278


LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8

1



Dimtype: fin de phase

Cutout dimension (mm): 55



21012 0288

LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8

2->3








Dimtype: fin de phase

Cutout dimension (mm): 55

REO X 93033 SI

202 25 811 932 A

	21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8	2 2	☐
	Dimtype: fin de phase Cutout dimension (mm): 48		
	21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68	2(2)	☐
	Dimtype: non dimmable Cutout dimension (mm): 60		
	21012 0500 LED POWER SUPPLY 500mA-DC / 24W IP68	2(1)	☐
	Dimtype: non dimmable Cutout dimension (mm): 60		
	21032 0295 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5	2	☐
	Dimtype: DALI Cutout dimension (mm): 30		
	21032 0305 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5	2	☐
	Dimtype: DALI Cutout dimension (mm): 30		

Notes: