



SPY 66 CLIP 92718



24621 9210 FW

AVAILABLE IN

NOIR-NOIR 24621 9210 B-B

ENTIÈREMENT BLANC 24621 9210 FW

BLANC-BLANC 24621 9210 W-W



[View on website](#)



General info	
LOCATION	interieur
INSTALLATION	Plafond Semi-encastré
CUTOUT SHAPE/SIZE (MM)	circulaire - 51
RECESSED DEPTH (MM)	40
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.6
ADJUSTABILITY	0° à 90° inclinable, 355° rotatif
INFORMATION	REFLECTOR SP-18° EXCLLED POWER SUPPLY 350-700mA-DC Optional REFLECTORS 30° & 45° available
Electrical info	
CLASS	III
DIM TYPE	selon le type d'alimentation externe
ENERGY CLASS	E
CERTIFICATION	CB, ENEC, LCA
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 11,6-25W / CRI>90 (R9: 60) / 2700K / 1458-2688lm
RVALUES	rf: 89 / Rg: 100
SDMC	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	18°
LED TECHNICS (LIGHT SOURCE)	2688lm // 25W // 108lm/W
LED TECHNICS (LUMINAIRE)	1920lm // 28,8W // 67lm/W

Remarks
GLASS / LENS 57: max. 500mA

Requirements
SPY 66 TUBE
LED POWER SUPPLY 350 / 500 / 700mA-DC DIM

Options
MOUNTING KIT FLUSH SPY

Accessories
HONEYCOMB 57
SPREAD LENS 57

DELTALIGHT

SPY 66 CLIP 92718

24621 9210 FW

LINEAR SPREAD LENS 57
SOFTENING LENS 57
GLASS SBL 57

For detailed installation instructions, please consult the manual : [24621_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 System ceiling	 414 90 01 - MOUNTING KIT FLUSH SPY Required
 Plasterboard	 414 90 01 - MOUNTING KIT FLUSH SPY Required
 Stucanet	 414 90 01 - MOUNTING KIT FLUSH SPY Required
 Wood	-
 Concrete	-
 Concrete + plaster	 414 90 01 - MOUNTING KIT FLUSH SPY Required
 Lintel + plaster	 414 90 01 - MOUNTING KIT FLUSH SPY Required
 Hollow-core slab	-
 Hollow-core slab + plaster	 414 90 01 - MOUNTING KIT FLUSH SPY Required
 Stretched ceiling	-











FINISH YOUR SPECIFICATION

les alimentations led	# of Fixtures
 web2print_power_supply_info_box	Min current Max current

DELTALIGHT

SPY 66 CLIP 92718











24621 9210 FW

	300 48 350 ED1	LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM1	1	☐
	Dimtype: 1 à 10 V			
	Cutout dimension (mm): 30			
	300 48 350 ED5	LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5	1	☐
	Dimtype: DALI			
	Cutout dimension (mm): 45			
	300 48 350 MDL	LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W MDL	1	☐
	Dimtype: non dimmable			
	Cutout dimension (mm): 30			
	300 48 350 WDL	LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W WDL	1	☐
	Dimtype: WDL = dimmable sans fil			
	Cutout dimension (mm): 45			
	300 48 500 ED1	LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM1	1	☐
	Dimtype: 1 à 10 V			
	Cutout dimension (mm): 30			
	300 48 500 ED5	LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5	1	☐
	Dimtype: DALI			
	Cutout dimension (mm): 45			
	300 48 500 MDL	LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W MDL	1	☐
	Dimtype: non dimmable			
	Cutout dimension (mm): 30			
	300 48 500 WDL	LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W WDL	1	☐
	Dimtype: WDL = dimmable sans fil			
	Cutout dimension (mm): 45			
	300 48 700 ED1	LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM1	1	☐
	Dimtype: 1 à 10 V			
	Cutout dimension (mm): 30			
	300 48 700 ED5	LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM5	1	☐
	Dimtype: DALI			
	Cutout dimension (mm): 45			

DELTALIGHT











SPY 66 CLIP 92718

24621 9210 FW

	300 48 700 MDL	LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W MDL	1	☐
Dimtype: non dimmable				
Cutout dimension (mm): 30				
	300 48 700 WDL	LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W WDL	1	☐
Dimtype: WDL = dimmable sans fil				
Cutout dimension (mm): 45				
	300 90 61	LED POWER SUPPLY MULTI-POWER DIM6	1 1 1	☐
Dimtype: fin de phase ou bouton poussoir				
Cutout dimension (mm): 56				
	300 90 63	LED POWER SUPPLY MULTI-POWER DIM9	2(2) 2(2) 2(1)	☐
Dimtype: 1 à 10 V ou DALI ou bouton poussoir				
Cutout dimension (mm): 82				
	300 90 64	LED POWER SUPPLY MULTI-POWER DIM7	1(1) 1(0) 1(0)	☐
Dimtype: 1 à 10 V ou bouton poussoir				
Cutout dimension (mm): 72				
	300 90 67	LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9	1 - 1	☐
Dimtype: 1 à 10 V ou DALI ou bouton poussoir				
	300 90 68	LED POWER SUPPLY MULTI-POWER DIM5	1(1) 1(0) 1(0)	☐
Dimtype: DALI				
Cutout dimension (mm): 72				
	300 90 69	LED POWER SUPPLY MULTI-POWER HV DIM9	3(3) 3(2) 2(1)	☐
Dimtype: 1 à 10 V ou DALI ou bouton poussoir				
Cutout dimension (mm): 84				
	300 90 124	LED POWER SUPPLY MULTI-POWER DIM7	1(1) 1(0) 0	☐
Dimtype: 1 à 10 V ou bouton poussoir				
Cutout dimension (mm): 55				
	300 90 125	LED POWER SUPPLY MULTI-POWER MINI DIM5	1(1) 1(0) 0	☐
Dimtype: DALI				
Cutout dimension (mm): 55				

SPY 66 CLIP 92718






24621 9210 FW

	300 90 135 LED POWER SUPPLY MULTI-POWER HV Dimtype: non dimmable Cutout dimension (mm): 90	2->2 2 2	☐
	21012 0010 LED POWER SUPPLY MULTI POWER Dimtype: non dimmable Cutout dimension (mm): 50	1 1 1	☐
	21012 0021 LED POWER SUPPLY MULTI POWER DIM1 Dimtype: 1 à 10 V Cutout dimension (mm): 54	1 1 1	☐
	21012 0035 LED POWER SUPPLY MULTI POWER DIM5 Dimtype: DALI Cutout dimension (mm): 54	1 1 1	☐
	21012 004W LED POWER SUPPLY MULTI-POWER WDL Dimtype: WDL = dimmable sans fil Cutout dimension (mm): 84	2(2) 2(2) 2(1)	☐
	21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL Dimtype: WDL = dimmable sans fil Cutout dimension (mm): 54	1 1 1	☐
	21012 0268 LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8 Dimtype: fin de phase Cutout dimension (mm): 50	1	☐
	21012 0288 LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8 Dimtype: fin de phase Cutout dimension (mm): 55	1 1	☐
	21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8 Dimtype: fin de phase Cutout dimension (mm): 48	1 1 0	☐
	21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68 Dimtype: non dimmable Cutout dimension (mm): 60	1(1)	☐

DELTALIGHT

SPY 66 CLIP 92718

24621 9210 FW

	21012 0490 LED POWER SUPPLY 700mA-DC / 30W IP68	1(0)	☐
Dimtype: non dimmable			
Cutout dimension (mm): 60			
	21012 0500 LED POWER SUPPLY 500mA-DC / 24W IP68	1(0)	☐
Dimtype: non dimmable			
Cutout dimension (mm): 60			
	21032 0295 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5	1	☐
Dimtype: DALI			
Cutout dimension (mm): 30			
	21032 0305 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5	1	☐
Dimtype: DALI			
Cutout dimension (mm): 30			
	21032 0315 LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM5	1	☐
Dimtype: DALI			
Cutout dimension (mm): 30			

kit de montage

	<u>414 90 01</u> MOUNTING KIT FLUSH SPY	☐
Cutout dimension (mm): 83		


modifier les dispositifs de lumière

	24611 0150 B HONEYCOMB 57 SINGLE USE B	☐
	24611 0160 GLASS SBL 57	☐


DELTALIGHT

SPY 66 CLIP 92718


24621 9210 FW




24611 0170 LINEAR SPREAD LENS 57

☐

24611 0190 SOFTENING LENS 57

☐


24611 0200 SPREAD LENS 57

☐

24611 0210 B HONEYCOMB 57 DOUBLE USE B

☐

Terminez votre produit



24611 0100 B SPY 66 TUBE B

☐

24611 0100 FBR SPY 66 TUBE FBR

☐

24611 0100 FG SPY 66 TUBE FG

☐

24611 0100 GC SPY 66 TUBE GC

☐

24611 0100 W SPY 66 TUBE W

☐

Réflecteur / lentille remplaçable



24611 0220 SPY 66 REFLECTOR 18°

☐

DELTALIGHT

SPY 66 CLIP 92718

24621 9210 FW



24611 0230 SPY 66 REFLECTOR 30°

☐

24611 0240 SPY 66 REFLECTOR 45°

☐

Notes: