



## LOGIC LINEAR ON 440 HONEYCOMB 94040 DIM5

30828 9435 A

AVAILABLE IN

**ALU GREY** 30828 9435 A

**BLACK** 30828 9435 B

**FLEMISH BRONZE OUTDOOR** 30828 9435 FBRX

**ANTHRACITE** 30828 9435 N

**WHITE** 30828 9435 W



[View on website](#)



### General info

|                                             |                                                                                        |
|---------------------------------------------|----------------------------------------------------------------------------------------|
| <b>LOCATION</b>                             | outdoor                                                                                |
| <b>INSTALLATION</b>                         | Floor Surface mounted, Wall Surface mounted                                            |
| <b>INGRESS PROTECTION</b>                   | IP67                                                                                   |
| <b>PROTECTION AGAINST MECHANICAL IMPACT</b> | IK07                                                                                   |
| <b>WEIGHT (KG)</b>                          | 1                                                                                      |
| <b>INFORMATION</b>                          | 8 x LENS WFL-40°<br>INCL.HONEYCOMB<br>EXCL.LED POWER SUPPLY 48V-DC<br>DALI DT8 dimming |

### Electrical info

|                     |          |
|---------------------|----------|
| <b>ELECTRICAL</b>   | 48V-DC   |
| <b>CLASS</b>        | III      |
| <b>DIM TYPE</b>     | DALI     |
| <b>ENERGY CLASS</b> | E        |
| <b>CERTIFICATES</b> | CB, ENEC |

### Lightsource info

|                                    |                                                      |
|------------------------------------|------------------------------------------------------|
| <b>LIGHTSOURCE NAME</b>            | LED                                                  |
| <b>LIGHTSOURCE</b>                 | LED cluster 14,4W / CRI>90 (R9: 64) / 4000K / 1949lm |
| <b>TM-30 VALUES</b>                | Rf: 91 / Rg: 100                                     |
| <b>SDCM</b>                        | SDCM3                                                |
| <b>RISKGROUP</b>                   | RG2                                                  |
| <b>LM80</b>                        | L80 > 150000                                         |
| <b>BEAMANGLE</b>                   | 40°                                                  |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | 1949lm // 14,4W // 131lm/W                           |
| <b>LED TECHNICS (LUMINAIRE)</b>    | 997lm // 16,6W // 60lm/W                             |

### Requirements

WALL BRACKET SET  
FLOOR BRACKET SET  
IP68 CABLE + CONNECTOR 5P  
LED POWER SUPPLY 48V-DC

### Options

THROUGH WIRING SET IP68

## LOGIC LINEAR ON 440 HONEYCOMB 94040 DIM5

30828 9435 A

For detailed installation instructions, please consult the manual : [30828\\_XXX5\\_HAND.pdf](#)

### FINISH YOUR SPECIFICATION

#### LED power supplies

#### # of Fixtures

**i** # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



**21032 0390** LED POWER SUPPLY 48V-DC / 90W

**Dimtype: non-dimmable**

**Cutout dimension (mm): 75**

5

#### Fixation components



**30810 0040**

LOGIC LINEAR 880 BOX EXTEND

**30810 0040 INOX** WALL BRACKET SET 60 INOX

**30810 0040 N**

WALL BRACKET SET 60 N




**30810 0050 INOX**

WALL BRACKET SET 100 INOX

**30810 0050 N**

WALL BRACKET SET 100 N



**30810 0060 INOX**

WALL BRACKET SET 200 INOX

**30810 0060 N**

WALL BRACKET SET 200 N

# DELTALIGHT

## LOGIC LINEAR ON 440 HONEYCOMB 94040 DIM5

30828 9435 A



**30810 0070 INOX** FLOOR BRACKET SET INOX

☐

### Electric connection parts



**30810 0080** IP68 CABLE + CONNECTOR 5P - 0,5m

☐

**30810 0090** IP68 CABLE + CONNECTOR 5P - 2m

☐

**30810 0100** THROUGH WIRING SET IP68 440

☐

Notes: