



OML50 - PRISMATIC LENS DU HE 1968mm 940

31643 9400 B

BESCHIKBAAR IN
ZWART 31643 9400 B



[Bekijk op website](#)



Algemene info

LOCATIE	binnen
STOF EN WATERDICHTHEID	IP20
GEWICHT (KG)	2.8
INFO	INCL LED POWER SUPPLY CABLING 1 CIRCUIT

Elektrische info

ELEKTRISCH	220-240V / 0 50-60Hz
KLASSE	I
VOEDING INBEGREPEN	YES
DIM TYPE	niet dimbaar
ENERGIE KLASSE	D
CERTIFICATES	EPD, RCM

Info lichtbron

LIGHTSOURCE NAME	LED
LICHTBRON	DOWN: LED cluster 29,2W / CRI>90 (R9: 50) / 4000K / 4990lm UP: LED cluster 24,5W / CRI>90 (R9: 50) / 4000K / 3965lm
TM-30 WAARDEN	Rf: 90 / Rg: 101
SMDC	SDCM3
RISK-GROEP	RG1
LM80	L80 > 60000
LED TECHNIEK (LICHTBRON)	DOWN: 4990lm // 29,2W // 171lm/W UP: 3965lm // 24,5W // 162lm/W

Notes: