



## M20/M26H - OCTAV 27 93030 DIM5

29014 9325 FG

AVAILABLE IN



**BLACK** 29014 9325 B

**FLEMISH BRONZE** 29014 9325 FBR

**FLEMISH GOLD** 29014 9325 FG

**GOLD COLOURED** 29014 9325 GC

**WHITE** 29014 9325 W



[View on website](#)



### General info

|                           |                                                                             |
|---------------------------|-----------------------------------------------------------------------------|
| <b>LOCATION</b>           | indoor                                                                      |
| <b>INSTALLATION</b>       | Low voltage systems Low voltage system mounted                              |
| <b>INGRESS PROTECTION</b> | IP20                                                                        |
| <b>WEIGHT (KG)</b>        | 0.3                                                                         |
| <b>ADJUSTABILITY</b>      | 0° to 85° swiveling, 355° rotatable                                         |
| <b>INFORMATION</b>        | REFLECTOR FL-30°<br>EXCLLED POWER SUPPLY 48V-DC<br>SPY 27 L TUBE B included |

### Electrical info

|                     |          |
|---------------------|----------|
| <b>ELECTRICAL</b>   | 48V-DC   |
| <b>CLASS</b>        | III      |
| <b>DIM TYPE</b>     | DALI     |
| <b>ENERGY CLASS</b> | E        |
| <b>CERTIFICATES</b> | CB, ENEC |

### Lightsource info

|                                    |                                                  |
|------------------------------------|--------------------------------------------------|
| <b>LIGHTSOURCE NAME</b>            | LED                                              |
| <b>LIGHTSOURCE</b>                 | LED array 5,8W / CRI>90 (R9: 52) / 3000K / 787lm |
| <b>TM-30 VALUES</b>                | rf: 90 / Rg: 99                                  |
| <b>SDCM</b>                        | SDCM1                                            |
| <b>RISKGROUPE</b>                  | RG1                                              |
| <b>LM80</b>                        | L90B10 > 50000                                   |
| <b>BEAMANGLE</b>                   | 30°                                              |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | 787lm // 5,8W // 135lm/W                         |
| <b>LED TECHNICS (LUMINAIRE)</b>    | 288lm // 6,7W // 43lm/W                          |

### Remarks

[Take a look at our MAGNETIC PROFILES movie](#)

### Requirements





LED POWER SUPPLY 48V-DC

For detailed installation instructions, please consult the manual : [29014\\_XXX5\\_HAND.pdf](#)

M20/M26H - OCTAV 27 93030 DIM5

29014 9325 FG

FINISH YOUR SPECIFICATION

| LED power supplies                                                                                                                                                                                                                                                                                                                                                         |    | # of Fixtures             |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----|---------------------------|
| <div><div></div><div># of fixtures indicates how many devices can be connected (min -&gt; max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.</div></div> |    | Min current   Max current |
| <div><div></div><div><b>300 89 48 100</b> LED POWER SUPPLY 48V-DC / 100W DIN</div><div>Dimtype: non-dimmable</div></div>                                                                                                                                                                   | 15 | <input type="text"/>      |
| <div><div></div><div><b>300 89 48 240</b> LED POWER SUPPLY 48V-DC / 240W DIN</div><div>Dimtype: non-dimmable</div></div>                                                                                                                                                                   | 36 | <input type="text"/>      |
| <div><div></div><div><b>21012 0230</b> LED POWER SUPPLY 48V-DC / 100W</div><div>Dimtype: non-dimmable</div><div>Cutout dimension (mm): 40</div></div>                                                                                                                                    | 15 | <input type="text"/>      |
| <div><div></div><div><b>21012 0240</b> LED POWER SUPPLY 48V-DC / 200W</div><div>Dimtype: non-dimmable</div><div>Cutout dimension (mm): 40</div></div>                                                                                                                                    | 30 | <input type="text"/>      |


COMPATIBLE COMPOSABLES

| SHIFTLINE M26H + SBL                                                                                                                                               | Available Colours                 |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------|
| <div><div></div><div><b>30411 9205</b> SHIFTLINE M26H + SBL 2m DIM5</div></div> | <div><div></div><div></div></div> |
| <div><div></div><div><b>30411 9305</b> SHIFTLINE M26H + SBL 2m DIM5</div></div> | <div><div></div><div></div></div> |
| <div><div></div><div><b>30412 9205</b> SHIFTLINE M26H + SBL 3m DIM5</div></div> | <div><div></div><div></div></div> |


# DELTALIGHT

## M20/M26H - OCTAV 27 93030 DIM5


29014 9325 FG



**30412 9305** SHIFTLINE M26H + SBL 3m DIM5



**30413 9205** SHIFTLINE M26H + SBL 4m DIM5




**30413 9305** SHIFTLINE M26H + SBL 4m DIM5




### SHIFTLINE M26H profile


### Available Colours




**23359 0000** SLM26H - PROFILE



**23359 0010** SLM26H - PROFILE 1m



**23359 0020** SLM26H - PROFILE 2m



**23359 0030** SLM26H - PROFILE 3m



### SPLITLINE M20 ST profile

### Available Colours



**23397 0000** SPM20 ST - PROFILE



**23397 0020** SPM20 ST - PROFILE 2m



# DELTALIGHT

## M20/M26H - OCTAV 27 93030 DIM5

29014 9325 FG




**23397 0030** SPM20 ST - PROFILE 3m




### SPLITLINE M20 profile


### Available Colours




**420 20 10 00** SPM20 - PROFILE 1m



**420 20 20 00** SPM20 - PROFILE 2m



**420 20 30 00** SPM20 - PROFILE 3m



**23301 0000** SPM20 - PROFILE B



Notes: