

**OML50 - LED ARRAY D HO  
CORNER R1675 45° 940**

31087 9400

[Bekijk op website](#)**Algemene info**

|                               |                                                                      |
|-------------------------------|----------------------------------------------------------------------|
| <b>LOCATIE</b>                | binnen                                                               |
| <b>STOF EN WATERDICHTHEID</b> | IP20                                                                 |
| <b>GEWICHT (KG)</b>           | 0                                                                    |
| <b>INFO</b>                   | CLUSTER DOWN: 4014lm/m<br>INCL.LED POWER SUPPLY<br>CABLING 1 CIRCUIT |

**Elektrische info**

|                           |                      |
|---------------------------|----------------------|
| <b>ELEKTRISCH</b>         | 220-240V / 0 50-60Hz |
| <b>KLASSE</b>             | I                    |
| <b>VOEDING INBEGREPEN</b> | YES                  |
| <b>DIM TYPE</b>           | niet dimbaar         |
| <b>ENERGIE KLASSE</b>     | D                    |
| <b>CERTIFICATES</b>       | EPD, RCM             |

**Info lichtbron**

|                                 |                                                      |
|---------------------------------|------------------------------------------------------|
| <b>LIGHTSOURCE NAME</b>         | LED                                                  |
| <b>LICHTBRON</b>                | LED cluster 32,6W / CRI>90 (R9: 50) / 4000K / 5286lm |
| <b>TM-30 WAARDEN</b>            | Rf: 90 / Rg: 101                                     |
| <b>SMDC</b>                     | SDCM3                                                |
| <b>RISK-GROEP</b>               | RG1                                                  |
| <b>LM80</b>                     | L80 > 60000                                          |
| <b>LED TECHNIEK (LICHTBRON)</b> | 5286lm // 32,6W // 162lm/W                           |

Notes: