DELTALIGHT




# COMPO L IP44 92720

**REFERENCE** 9 15755 9220 DC

AVAILABLE IN
**BLACK** 9 15755 9220 B
**CHROMED** 9 15755 9220 C
**DARK CHROMED** 9 15755 9220 DC
**WHITE** 9 15755 9220 W







View on website

| General info | |
|---|---|
| **LOCATION** | indoor-outdoor |
| **INSTALLATION** | Ceiling Recessed |
| **CUTOUT SHAPE/SIZE (MM)** | round - 135 |
| **RECESSED DEPTH (MM)** | 130 |
| **THICKNESS OF MOUNTING SURFACE (MM)** | max.25 |
| **INGRESS PROTECTION** | IP44/20 |
| **WEIGHT (KG)** | 0.476 |
| **ADJUSTABILITY** | 0° to 30° swiveling, 355° rotatable |

| Electrical info | |
|---|---|
| **CLASS** | III |
| **DIM TYPE** | depending on power supply |
| **ENERGY CLASS** | F |

| Lightsource info | |
|---|---|
| **LIGHTSOURCE NAME** | LED |
| **LIGHTSOURCE** | LED array 17,2W / CRI>90 (R9: 60) / 2700K / 2009lm |
| **TM-30 VALUES** | Rf: 89 / Rg: 100 |
| **SDCM** | SDCM1 |
| **RISKGROUP** | RG1 |
| **LM80** | L90B10 > 50000 |
| **BEAMANGLE** | 20° |
| **LED TECHNICS (LIGHT SOURCE)** | 2009lm // 17,2W // 117lm/W |
| **LED TECHNICS (LUMINAIRE)** | 1487lm // 20W // 75lm/W |

**Requirements**

LED POWER SUPPLY 500 mA - DC

**Accessories**

COMPO L HONEYCOMB SINGLE USE B
COMPO L LINEAR SPREAD LENS
COMPO L SPREAD LENS
COMPO L SOFTENING LENS
COMPO L GLASS SBL

For detailed installation instructions, please consult the manual : **9_15755_XXX0_HAND.pdf**

DELTALIGHT

# COMPO L IP44 92720

9 15755 9220 DC

## CEILING COMPATIBILITY

| Ceiling Type | Mounting Kit | |
|---|---|---|
|  System ceiling | 15710 0030 - MOUNTING KIT COMPO L TRIM | Required |
| | 15710 0060 - MOUNTING KIT COMPO L TRIMLESS | Required |
|  Plasterboard | 15710 0030 - MOUNTING KIT COMPO L TRIM | Required |
| | 15710 0060 - MOUNTING KIT COMPO L TRIMLESS | Required |
|  Wood | 15710 0030 - MOUNTING KIT COMPO L TRIM | Required |
| | 15710 0060 - MOUNTING KIT COMPO L TRIMLESS | Required |

## FINISH YOUR SPECIFICATION

| LED Power supply | | # of Fixtures |
|---|---|---|
| | | Min current \| Max current |
| **15710 3200** | LED POWER SUPPLY MULTIPOWER 15W NO DIM 300mA | 1->2 |
| **15710 3600** | LED POWER SUPPLY MULTIPOWER 20W NO DIM 500mA | 1 |
| **15710 3700** | LED POWER SUPPLY MULTIPOWER 10W DIM8 300mA | 1 |
| **15710 4200** | LED POWER SUPPLY MULTIPOWER 20W DIM8 500mA | 1 |
| **15710 4400** | LED POWER SUPPLY MULTIPOWER 12W DIM1 300mA | 1->2 |
| **15710 4700** | LED POWER SUPPLY MULTIPOWER 20W DIM1 500mA | 1 |
| **15710 5200** | LED POWER SUPPLY MULTIPOWER 12W DALI DT6 300mA | 1->2 |
| **Dimtype: DALI** | | |
| **15710 5400** | LED POWER SUPPLY MULTIPOWER 20W DALI DT6 500mA | 1 |
| **Dimtype: DALI** | | |

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

DELTALIGHT

# COMPO L IP44 92720

9 15755 9220 DC

## Mounting kits




**15710 0030 B** MOUNTING KIT COMPO L TRIM B ☐

**Cutout dimension (mm): 92**

**15710 0030 W** MOUNTING KIT COMPO L TRIM W ☐




**15710 0060** MOUNTING KIT COMPO L TRIMLESS ☐

**Cutout dimension (mm): 92**

## Light altering devices

**15710 2100 B** COMPO L HONEYCOMB SINGLE USE B ☐

**15710 2110** COMPO L LINEAR SPREAD LENS ☐

**Cutout dimension (mm): 42**

**15710 2120** COMPO L SPREAD LENS ☐

**Cutout dimension (mm): 42**

**15710 2130** COMPO L SOFTENING LENS ☐

**Cutout dimension (mm): 42**

**15710 2140** COMPO L GLASS SBL ☐

**Cutout dimension (mm): 42**

Notes: