



## OML50 C - LED ARRAY UP HE 2296mm 930 DIM5

31141 9305

 [View on website](#)



| General info                       |  |
|------------------------------------|--|
| <b>LOCATION</b>                    | indoor   |
| <b>INGRESS PROTECTION</b>          | IP20   |
| <b>WEIGHT (KG)</b>                 | 1  |
| <b>INFORMATION</b>                 | CLUSTER UP: 1932lm/m<br>INCL.DIMMABLE LED POWER SUPPLY<br>(DALI-2 standard)<br>CABLING 1 CIRCUIT |
| Electrical info                    |  |
| <b>ELECTRICAL</b>                  | 220-240V / 0 50-60Hz   |
| <b>CLASS</b>                       | I  |
| <b>POWER SUPPLY</b>                | YES  |
| <b>DIM TYPE</b>                    | DALI   |
| <b>ENERGY CLASS</b>                | D  |
| <b>CERTIFICATES</b>                | EPD, RCM   |
| Lightsource info                   |  |
| <b>LIGHTSOURCE NAME</b>            | LED  |
| <b>LIGHTSOURCE</b>                 | LED cluster 28,6W / CRI>90 (R9: 50) / 3000K / 4435lm   |
| <b>TM-30 VALUES</b>                | Rf: 92 / Rg: 100   |
| <b>SDCM</b>                        | SDCM3  |
| <b>RISKGROUP</b>                   | RG1  |
| <b>LM80</b>                        | L80 > 60000  |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | 4435lm // 28,6W // 155lm/W   |

### Options

WIRELESS CONTROL DIM5

Notes: