
DELTALIGHT




SOLI - 66 92745 DIM5

REFERENCE 27123 9235 B

AVAILABLE IN
BLACK 27123 9235 B
WHITE 27123 9235 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	0° to 90° swiveling, 360° rotatable
INFORMATION	REFLECTOR WFL-45° EXCL.LED POWER SUPPLY 48V-DC Optional REFLECTORS 18° & 30° available

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, LCA

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 21W / CRI>90 (R9: 60) / 2700K / 2356lm
TM-30 VALUES	Rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	45°
LED TECHNICS (LIGHT SOURCE)	2356lm // 21W // 112lm/W
LED TECHNICS (LUMINAIRE)	1617lm // 24,2W // 67lm/W

Requirements

SPY 66 TUBE
LED POWER SUPPLY 48V-DC

Accessories

HONEYCOMB 57
SPREAD LENS 57
LINEAR SPREAD LENS 57
SOFTENING LENS 57
GLASS SBL 57

DELTALIGHT

SOLI - 66 92745 DIM5

27123 9235 B

For detailed installation instructions, please consult the manual : **27123_XXX5_HAND.pdf**


FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures


Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.




300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN — 4 ☐

Dimtype: non-dimmable



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN — 10 ☐


Dimtype: non-dimmable



21012 0230 LED POWER SUPPLY 48V-DC / 100W — 4 ☐

Dimtype: non-dimmable

Cutout dimension (mm): 40




21012 0240 LED POWER SUPPLY 48V-DC / 200W — 8 ☐


Dimtype: non-dimmable

Cutout dimension (mm): 40

Light altering devices



24611 0150 B HONEYCOMB 57 SINGLE USE B — ☐




24611 0160 GLASS SBL 57 — ☐


DELTALIGHT

SOLI - 66 92745 DIM5


27123 9235 B




24611 0170 LINEAR SPREAD LENS 57



24611 0190 SOFTENING LENS 57




24611 0200 SPREAD LENS 57



24611 0210 B HONEYCOMB 57 DOUBLE USE B

Finish your product



24611 0100 B SPY 66 TUBE B

24611 0100 FBR SPY 66 TUBE FBR

24611 0100 FG SPY 66 TUBE FG

24611 0100 GC SPY 66 TUBE GC

24611 0100 W SPY 66 TUBE W

Replaceable reflector / lens



24611 0220 SPY 66 REFLECTOR 18°

DELTALIGHT

SOLI - 66 92745 DIM5

27123 9235 B





24611 0230 SPY 66 REFLECTOR 30°



24611 0240 SPY 66 REFLECTOR 45°

COMPATIBLE COMPOSABLES

SOLISCAPE profile	Available Colours
 **27111 0020** SOLI - PROFILE 2m	
 **27111 0030** SOLI - PROFILE 3m	

Notes: