



LOGIC LINEAR 880 93025 DIM5

30814 9325 N

AVAILABLE IN
ANTHRACITE 30814 9325 N



[View on website](#)




General info	
LOCATION	outdoor
INSTALLATION	Floor Recessed
CUTOUT SHAPE/SIZE (MM)	rectangle - BOX
RECESSED DEPTH (MM)	140
INGRESS PROTECTION	IP67
PROTECTION AGAINST MECHANICAL IMPACT	IK09
WEIGHT (KG)	3.8
ADJUSTABILITY	non adjustable
INFORMATION	16 x LENS FL-25° INCL.DIMMABLE LED POWER SUPPLY 650mA-DC INCL.1 x CABLE H07 RN-F 5 x 1mm² 0,5m INCL.IP68 CONNECTOR 5P ESG 8mm max.500kg
Electrical info	
ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD, RCM
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 28,8W / CRI>90 (R9: 64) / 3000K / 3597lm
TM-30 VALUES	Rf: 92 / Rg: 99
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 150000
BEAMANGLE	25°
LED TECHNICS (LIGHT SOURCE)	3597lm // 28,8W // 121lm/W
LED TECHNICS (LUMINAIRE)	2544lm // 33,1W // 77lm/W
Requirements	
LOGIC LINEAR BOX	

For detailed installation instructions, please consult the manual : [30814_XXX5_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Ground mounting boxes




30810 0030 LOGIC LINEAR 880 BOX

Cutout dimension (mm): 920 x 150

☐

Waterproof connection parts



21034 0150 IP68 Y-CONNECTOR 5P

☐

Notes: