



HALOSCAN ON 1 MP 92721 DIM8

REFERENCE



23147 9228 W-W

AVAILABLE IN

NOIR-NOIR 23147 9228 B-B

NOIR-COULEUR OR 23147 9228 B-GC

BLANC-BLANC 23147 9228 W-W



[View on website](#)



General info

LOCATION	interieur
INSTALLATION	Plafond Applique
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	0° à 45° inclinable, 355° rotatif
INFORMATION	LENS FL-21° INCL.DIMMABLE LED POWER SUPPLY 500mA-DC

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY INCLUDED	YES
DIM TYPE	fin de phase
ENERGY CLASS	D
CERTIFICATION	CB, ENEC, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 60) / 2700K / 1041lm
RVALUES	Rf: 89 / Rg: 100
SDMC	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	21°
LED TECHNICS (LIGHT SOURCE)	1041lm // 8,6W // 121lm/W
LED TECHNICS (LUMINAIRE)	812lm // 9,9W // 82lm/W

Accessories

HALOSCAN HONEYCOMB
HALOSCAN LINEAR SPREAD LENS
HALOSCAN KAP MP

For detailed installation instructions, please consult the manual : [23147_XXX8_HAND.pdf](#)




DELTALIGHT

HALOSCAN ON 1 MP 92721 DIM8

23147 9228 W-W

FINISH YOUR SPECIFICATION

modifier les dispositifs de lumière

	23110 0040	HALOSCAN LINEAR SPREAD LENS	☐
	23110 0050 B	HALOSCAN HONEYCOMB B	☐
	23110 0060 B	HALOSCAN KAP MP B	☐
	23110 0060 W	HALOSCAN KAP MP W	☐

Notes: