


INFORM ST 1380 93067

REFERENCE 25503 9320 W-B

AVAILABLE IN
BLACK-BLACK 25503 9320 B-B
BLACK-FLEMISH GOLD 25503 9320 B-FG
WHITE-BLACK 25503 9320 W-B
WHITE-WHITE 25503 9320 W-W



 [View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	rectangle - 38 x 1393
RECESSED DEPTH (MM)	40
THICKNESS OF MOUNTING SURFACE (MM)	max.12,5
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.2
ADJUSTABILITY	non adjustable
INFORMATION	60 x REFLECTOR FL-67° EXCL.LED POWER SUPPLY 500/750mA-DC

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 17,6-27,9W / CRI>90 (R9: 50) / 3000K / 2670-3858lm
TM-30 VALUES	Rf: 92 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
BEAMANGLE	67°
LED TECHNICS (LIGHT SOURCE)	3858lm // 27,9W // 138lm/W
LED TECHNICS (LUMINAIRE)	3368lm // 32,1W // 105lm/W



Requirements	
INFORM POWER SUPPLY 45W	

For detailed installation instructions, please consult the manual : [25503_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
	System ceiling -
	Plasterboard -
	Wood -

FINISH YOUR SPECIFICATION

LED power supplies		# of Fixtures
 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		Min current Max current
	25510 0385 INFORM POWER SUPPLY 45W DIM5 Dimtype: DALI	1
	25510 0430 INFORM POWER SUPPLY 45W Dimtype: non-dimmable	1

Notes: