



## OML50 - PRISMATIC LENS DU HE 1968mm 940 DIM5

31643 9405 B

AVAILABLE IN  
**BLACK** 31643 9405 B



[View on website](#)



### General info

<b>LOCATION</b>	indoor
<b>INGRESS PROTECTION</b>	IP20
<b>WEIGHT (KG)</b>	2.8
<b>INFORMATION</b>	INCL.DIMMABLE LED POWER SUPPLY (DALI-2 standard) CABLING 1 CIRCUIT

### Electrical info

<b>ELECTRICAL</b>	220-240V / 0 50-60Hz
<b>CLASS</b>	I
<b>POWER SUPPLY</b>	YES
<b>DIM TYPE</b>	DALI
<b>ENERGY CLASS</b>	D
<b>CERTIFICATES</b>	EPD, RCM

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	DOWN: LED cluster 29,2W / CRI>90 (R9: 50) / 4000K / 4990lm UP: LED cluster 24,5W / CRI>90 (R9: 50) / 4000K / 3965lm
<b>TM-30 VALUES</b>	Rf: 90 / Rg: 101
<b>SDCM</b>	SDCM3
<b>RISKGROUP</b>	RG1
<b>LM80</b>	L80 > 60000
<b>LED TECHNICS (LIGHT SOURCE)</b>	DOWN: 4990lm // 29,2W // 171lm/W UP: 3965lm // 24,5W // 162lm/W

### Options

WIRELESS CONTROL DIM5

Notes: