

**OML50 - LED ARRAY D HO  
CORNER R2925 45° 930**

31088 9300

[Bekijk op website](#)**Algemene info**

<b>LOCATIE</b>	binnen
<b>STOF EN WATERDICHTHEID</b>	IP20
<b>GEWICHT (KG)</b>	0
<b>INFO</b>	CLUSTER DOWN: 3848lm/m INCL.LED POWER SUPPLY CABLING 1 CIRCUIT

**Elektrische info**

<b>ELEKTRISCH</b>	220-240V / 0 50-60Hz
<b>KLASSE</b>	I
<b>VOEDING INBEGREPEN</b>	YES
<b>DIM TYPE</b>	niet dimbaar
<b>ENERGIE KLASSE</b>	D
<b>CERTIFICATES</b>	EPD, RCM

**Info lichtbron**

<b>LIGHTSOURCE NAME</b>	LED
<b>LICHTBRON</b>	LED cluster 57,1W / CRI>90 (R9: 50) / 3000K / 8870lm
<b>TM-30 WAARDEN</b>	Rf: 92 / Rg: 100
<b>SMDC</b>	SDCM3
<b>RISK-GROEP</b>	RG1
<b>LM80</b>	L80 > 60000
<b>LED TECHNIEK (LICHTBRON)</b>	8870lm // 57,1W // 155lm/W

Notes: