



OML50 - INFORM DU HO 3280mm 8+16+8LED 93063 DIM5

31438 9335 B

BESCHIKBAAR IN
ZWART 31438 9335 B



[Bekijk op website](#)



Algemene info

LOCATIE	binnen
STOF EN WATERDICHTHEID	IP20
GEWICHT (KG)	3.3
INFO	CLUSTER DOWN: 2131lm/m CLUSTER UP: 2663lm/m INCL.DIMMABLE LED POWER SUPPLY (DALI-2 standard) CABLING 1 CIRCUIT

Elektrische info

INGANGSSPANNING	220-240V / 0 50-60Hz
KLASSE	I
VOEDING	YES
DIM TYPE	DALI
ENERGIE KLASSE	E
CERTIFICATEN	EPD, RCM

Info lichtbron

LIGHTSOURCE NAME	LED
LICHTBRON	DOWN: LED cluster 48,4W / CRI>90 (R9: 50) / 3000K / 6989lm UP: LED cluster 60,5W / CRI>90 (R9: 50) / 3000K / 8736lm
TM-30-15 WAARDEN	Rf: 92 / Rg: 100
SDCM	SDCM3
RISK-GROEP	RG1
LM80	L80 > 60000
BEAMANGLE	63°
LED TECHNIEK (LICHTBRON)	DOWN: 6989lm // 48,4W // 145lm/W UP: 8736lm // 60,5W // 145lm/W

Opties

WIRELESS CONTROL DIM5

Notes: