





M - DOT.COM WALLWASH 02 930 HO DIM5

23367 9305 B

AVAILABLE IN
BLACK 23367 9305 B



[View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	non adjustable
INFORMATION	EXCL.LED POWER SUPPLY 48V-DC
Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	F
CERTIFICATES	CB, ENEC, EPD
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 9,6W / CRI>90 (R9: 68) / 3000K / 1068lm
TM-30 VALUES	Rf: 89 / Rg: 97
SDCM	SDCM3
LM80	L70 > 60000
LED TECHNICS (LIGHT SOURCE)	1068lm // 9,6W // 111lm/W
LED TECHNICS (LUMINAIRE)	581lm // 11W // 53lm/W

Remarks

Take a look at our [MAGNETIC PROFILES movie](#)

Requirements

LED POWER SUPPLY 48V-DC

For detailed installation instructions, please consult the manual : [23367_9205_HAND.pdf](#)

FINISH YOUR SPECIFICATION

LED power supplies		# of Fixtures
# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		Min current Max current
171 38 63	300 89 48 90 LED POWER SUPPLY 48V-DC / 90W Dimtype: non-dimmable Cutout dimension (mm): 75	7
55 100 90	300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN Dimtype: non-dimmable	8
240 49 60	300 89 48 150 LED POWER SUPPLY 48V-DC / 150W Dimtype: non-dimmable	12
63 114 125	300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN Dimtype: non-dimmable	20
17 298 30	21012 0230 LED POWER SUPPLY 48V-DC / 100W Dimtype: non-dimmable Cutout dimension (mm): 40	8
22 392 30	21012 0240 LED POWER SUPPLY 48V-DC / 200W Dimtype: non-dimmable Cutout dimension (mm): 40	17


COMPATIBLE COMPOSABLES

SHIFTLINE M26 profile	Available Colours
50 26	420 26 10 00 SLM26 - PROFILE 1m


DELTALIGHT

M - DOT.COM WALLWASH 02 930 HO DIM5

23367 9305 B



420 26 20 00 SLM26 - PROFILE 2m



420 26 30 00 SLM26 - PROFILE 3m



SHIFTLINE M26H + SBL

Available Colours



30411 9205 SHIFTLINE M26H + SBL 2m DIM5




30411 9305 SHIFTLINE M26H + SBL 2m DIM5




30412 9205 SHIFTLINE M26H + SBL 3m DIM5



30412 9305 SHIFTLINE M26H + SBL 3m DIM5



30413 9205 SHIFTLINE M26H + SBL 4m DIM5




30413 9305 SHIFTLINE M26H + SBL 4m DIM5



SHIFTLINE M26H profile

Available Colours






23359 0000 SLM26H - PROFILE



DELTALIGHT

M - DOT.COM WALLWASH 02 930 HO DIM5

23367 9305 B

	23359 0010 SLM26H - PROFILE 1m	
	23359 0020 SLM26H - PROFILE 2m	
	23359 0030 SLM26H - PROFILE 3m	




SPLITLINE M20 ST profile

Available Colours

	23397 0000 SPM20 ST - PROFILE	
	23397 0020 SPM20 ST - PROFILE 2m	
	23397 0030 SPM20 ST - PROFILE 3m	


SPLITLINE M20 profile

Available Colours

	420 20 10 00 SPM20 - PROFILE 1m	
	420 20 20 00 SPM20 - PROFILE 2m	
	420 20 30 00 SPM20 - PROFILE 3m	

M - DOT.COM WALLWASH 02 930 HO DIM5

23367 9305 B



23301 0000 SPM20 - PROFILE B



Notes: