

OML50 - LED ARRAY D HO CORNER R2925 45° 940 DIM5

31088 9405

 [Bekijk op website](#)


| Algemene info | |
|---------------------------------|--|
| LOCATIE | binnen |
| STOF EN WATERDICHTHEID | IP20 |
| GEWICHT (KG) | 0 |
| INFO | CLUSTER DOWN: 4014lm/m INCL.DIMMABLE LED POWER SUPPLY (DALI-2 standard) CABLING 1 CIRCUIT |
| Elektrische info | |
| ELEKTRISCH | 220-240V / 0 50-60Hz |
| KLASSE | I |
| VOEDING INBEGREPEN | YES |
| DIM TYPE | DALI |
| ENERGIE KLASSE | D |
| CERTIFICATES | EPD, RCM |
| Info lichtbron | |
| LIGHTSOURCE NAME | LED |
| LICHTBRON | LED cluster 57,1W / CRI>90 (R9: 50) / 4000K / 925lm |
| TM-30 WAARDEN | Rf: 90 / Rg: 101 |
| SMDC | SDCM3 |
| RISK-GROEP | RG1 |
| LM80 | L80 > 60000 |
| LED TECHNIEK (LICHTBRON) | 925lm // 57,1W // 162lm/W |

Opties

WIRELESS CONTROL DIM5

Notes: