



OML50 - INFORM DU HO 3280mm 8+16+8LED 94063

31438 9430 B

BESCHIKBAAR IN
ZWART 31438 9430 B



[Bekijk op website](#)



Algemene info	
LOCATIE	binnen
STOF EN WATERDICHTHEID	IP20
GEWICHT (KG)	2.7
INFO	CLUSTER DOWN: 2221lm/m CLUSTER UP: 2776lm/m INCLLED POWER SUPPLY CABLING 1 CIRCUIT
Elektrische info	
ELEKTRISCH	220-240V / 0 50-60Hz
KLASSE	I
VOEDING INBEGREPEN	YES
DIM TYPE	niet dimbaar
ENERGIE KLASSE	D
CERTIFICATES	EPD, RCM
Info lichtbron	
LIGHTSOURCE NAME	LED
LICHTBRON	DOWN: LED cluster 48,4W / CRI>90 (R9: 50) / 4000K / 7283lm UP: LED cluster 60,5W / CRI>90 (R9: 50) / 4000K / 9104lm
TM-30 WAARDEN	Rf: 90 / Rg: 101
SMD	SDCM3
RISK-GROEP	RG1
LM80	L80 > 60000
BEAMANGLE	63°
LED TECHNIEK (LICHTBRON)	DOWN: 7283lm // 48,4W // 151lm/W UP: 9104lm // 60,5W // 151lm/W

Notes: