M-OBIN



Introducing Obin, a cutting-edge lighting solution that embodies our commitment to quality and innovation. Based on the patented ERS (Ex-Centriq Rotation System) and equipped with flat lenses, Obin fuses ultimate flexibility with supreme user comfort in a minimalistic surface mounted lighting fixture.
By adjusting the rounded backside - using the ERS system - Obin is 360° rotatable and 45° tiltable without the need of an additional hinge. On the frontside, the sleek lenses create a sense of depth without the need of real physical space.

Specification	
LED Aperture:	$1^{1}/_{16}$"
Adjustability:	0° - 45° / 360°
Rating:	Damp

Performance	
CRI / TM-30 (3000K):	90 / Rf: 90 / Rg: 99
SDCM:	1
LED Maintenance:	L90B10>50,000h
*High Power:	13.3W

Delivered Lumens	2700K		3000K		3500K	
**Optic:	MS	MD	MS	MD	MS	MD
M-Obin:	1217	1258	1272	1315	1318	1362

Listing
ETL certified to US and Canadian safety standards.

Warranty
5-year limited warranty.

Ordering
ALL BOXES MUST BE FILLED IN TO CORRECTLY ORDER

Example: OBN1-HPMS27A-B-GC-M20H-MDL

Luminaire	Size	Power*	Optic**	CCT	Function	Finish	Inner Finish	Application[1]	Controls
OBN OBIN	**1** Single Spot	**HP** High Power	**MS** Medium Narrow Spot 24° **MD** Medium Spot 36°	**27** 2700K **30** 3000K **35** 3500K	**A** Adjustable	**B** Black **BRA** Brushed Aluminum **BRAT** Brushed Anthracite **BRG** Brushed Gold **BROB** Brushed Old Bronze **W** White	**B** Black **DC** Dark Chromed **FBR** Flemish Bronze **FG** Flemish Gold **GC** Gold Colored **W** White	**M20H** Shiftline M26H / Shiftline M26H + SBL[2] / Splitline M20 / Splitline M20 ST Profile	**MDL**[2] 0-10V dim via Modulator **D5** Dali dim **WD**[2] Wireless dim


1 Profile system hardware specified separately.
2 Shiftline M26H + SBL only available with Controls D5.

Related Products


M-Spy 39 (spotlight with same finish options), Obin, M-Haloscan (similar scale), Haloscan (similar scale)


Finish Options


M-OBIN





For Application M20H



BLACK
(shown in Splitline M20)


BRUSHED
ALUMINUM
(shown in Splitline M20)



BRUSHED
ANTHRACITE
(shown in Splitline M20)


BRUSHED
GOLD
(shown in Splitline M20)


BRUSHED
OLD BRONZE
(shown in Splitline M20)


WHITE
(shown in Splitline M20)

INNER FINISH



For Application M20H


BLACK


DARK
CHROMED



FLEMISH
BRONZE


FLEMISH
GOLD


GOLD
COLORED


WHITE


Accessories




HONEYCOMB 75
19810 0110 B

Photometric Data

OBIN



MS 24°



MD 36°

Installation Options

Deltalight's Magnetic Systems all utilize 48V remote power supplies. With a maximum of 96W per power supply, the below details maximum magnetic modules per power feed.

Maximum Capacity per Remote Power Supply	M-Obin
*High Power:	6

FOR SYSTEM HARDWARE, REFER TO THE FOLLOWING PROFILE SYSTEMS:
Shiftline M26H (surface/suspended, high-height, optional curved corner connectors)
Shiftline M26H + SBL (surface/suspended, high-height, integral continuous light line)
Splitline M20 (recessed, knife-edge, optional curved corner connectors)
Splitline M20 ST (recessed, small trim)

As technology changes, please use information above as guidance. For most recent updated information please contact factory. Specifications subject to change without notice.

DELTALIGHT