


M - WIRELESS CONTROL DIM5

21032 0085



[View on website](#)



General info	
LOCATION	indoor
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.1
INFORMATION	To control magnetic modules with DALI drivers via CTRL DELTA up to 64 modules (lamps - control gear) divided into 8 groups.
Electrical info	
CLASS	III
DIM TYPE	WDL = wireless dimmable

Remarks

[Click here for more information concerning Wireless Control by CTRL DELTA](#)

For detailed installation instructions, please consult the manual : [21032_0085_HAND.pdf](#)

WHERE USED

420 20 10 00	SPM20 - PROFILE 1m
420 20 20 00	SPM20 - PROFILE 2m
420 20 30 00	SPM20 - PROFILE 3m
23301 0000	SPM20 - PROFILE
23358 0000	SLM26L - PROFILE
23358 0010	SLM26L - PROFILE 1m
23358 0020	SLM26L - PROFILE 2m
23358 0030	SLM26L - PROFILE 3m
23359 0000	SLM26H - PROFILE
23359 0010	SLM26H - PROFILE 1m
23359 0020	SLM26H - PROFILE 2m
23359 0030	SLM26H - PROFILE 3m
23374 0000	SLM44 - PROFILE
23374 0020	SLM44 - PROFILE 2m
23374 0030	SLM44 - PROFILE 3m
23397 0000	SPM20 ST - PROFILE
23397 0020	SPM20 ST - PROFILE 2m
23397 0030	SPM20 ST - PROFILE 3m

DELTALIGHT

M - WIRELESS CONTROL DIM5

21032 0085

Notes: