
DELTALIGHT

M - WIRELESS CONTROL DIM5

REFERENCE 21032 0085



View on website

General info	
LOCATION	interieur
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.1
INFORMATION	To control magnetic modules with DALI drivers via CTRL DELTA up to 64 modules (lamps - control gear) divided into 8 groups.

Electrical info	
CLASS	III
DIM TYPE	WDL = dimmable sans fil

Remarks

Click here for more information concerning Wireless Control by CTRL DELTA

For detailed installation instructions, please consult the manual : **21032_0085_HAND.pdf**

WHERE USED

420 20 10 00	SPM20 - PROFILE 1m
420 20 20 00	SPM20 - PROFILE 2m
420 20 30 00	SPM20 - PROFILE 3m
23301 0000	SPM20 - PROFILE
23358 0000	SLM26L - PROFILE
23358 0010	SLM26L - PROFILE 1m
23358 0020	SLM26L - PROFILE 2m
23358 0030	SLM26L - PROFILE 3m
23359 0000	SLM26H - PROFILE
23359 0010	SLM26H - PROFILE 1m
23359 0020	SLM26H - PROFILE 2m
23359 0030	SLM26H - PROFILE 3m
23374 0000	SLM44 - PROFILE
23374 0020	SLM44 - PROFILE 2m
23374 0030	SLM44 - PROFILE 3m
23397 0000	SPM20 ST - PROFILE
23397 0020	SPM20 ST - PROFILE 2m
23397 0030	SPM20 ST - PROFILE 3m

DELTALIGHT

M - WIRELESS CONTROL DIM5

21032 0085

Notes: