



DEEP RINGO HE 94020

19440 9420 FG

AVAILABLE IN

BLACK 19440 9420 B

BRUSHED ALU 19440 9420 BRA

BRUSHED ANTHRACITE 19440 9420 BRAT

BRUSHED BROWN BRONZE 19440 9420 BRBB

BRUSHED COPPER 19440 9420 BRCU

BRUSHED GOLD 19440 9420 BRG

BRUSHED OLD BRONZE 19440 9420 BROB

CREAM 19440 9420 CR

FLEMISH BRONZE 19440 9420 FBR

FLEMISH GOLD 19440 9420 FG

GOLD COLOURED 19440 9420 GC

PIANO BLACK 19440 9420 PB

WHITE 19440 9420 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 76
RECESSED DEPTH (MM)	90
THICKNESS OF MOUNTING SURFACE (MM)	min.5
INGRESS PROTECTION	IP43/20
WEIGHT (KG)	0.2
ADJUSTABILITY	non adjustable
INFORMATION	LENS FL-20° EXCL.LED POWER SUPPLY 350mA-DC

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	D
CERTIFICATES	EPD, LCA

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 6W / CRI>90 (R9: 60) / 4000K / 975lm
TM-30 VALUES	rf: 96 / Rg: 99
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	20°
LED TECHNICS (LIGHT SOURCE)	975lm // 6W // 163lm/W
LED TECHNICS (LUMINAIRE)	834lm // 6,9W // 121lm/W

Remarks

High Efficacy : > 100lm/W

Requirements

LED POWER SUPPLY 350mA-DC DIM

DELTALIGHT

DEEP RINGO HE 94020

19440 9420 FG

For detailed installation instructions, please consult the manual : [19440_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Stucanet	-
 Wood	-
 Concrete	-
 Concrete + plaster	-
 Lintel + plaster	-
 Hollow-core slab	-
 Hollow-core slab + plaster	-
 Stretched ceiling	-

FINISH YOUR SPECIFICATION






Emergency units

	21032 0270 B EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER B	☐
	21032 0270 W EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER W	☐

DELTALIGHT

DEEP RINGO HE 94020

19440 9420 FG

LED power supplies		# of Fixtures
 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		Min current Max current
 300 90 91 LED POWER SUPPLY 350mA-DC / 15W		2(1) ☐
Dimtype: non-dimmable Cutout dimension (mm): 40		
 300 90 110 LED POWER SUPPLY 350mA-DC / 10W DIM8		1 ☐
Dimtype: mains (phase cut-off) Cutout dimension (mm): 42		
 300 90 116 LED POWER SUPPLY 350mA-DC / 18W DIM8		2->2 ☐
Dimtype: mains (phase cut-off) Cutout dimension (mm): 55		
 21012 0515 LED POWER SUPPLY MULTI POWER DIM5		1(1) ☐
Dimtype: DALI Cutout dimension (mm): 55		
 21012 0520 LED POWER SUPPLY 350mA-DC / 8W		1(0) ☐
Dimtype: non-dimmable Cutout dimension (mm): 47		
 21012 0575 LED POWER SUPPLY MULTI POWER DIM5		2->3(2) ☐
Dimtype: DALI Cutout dimension (mm): 55		

Notes: