
DELTALIGHT




M20/M26H - OCTAV 39 92740 MDL

REFERENCE 29020 9230 FG

AVAILABLE IN
BLACK 29020 9230 B
FLEMISH BRONZE 29020 9230 FBR
FLEMISH GOLD 29020 9230 FG
GOLD COLOURED 29020 9230 GC
WHITE 29020 9230 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.4
ADJUSTABILITY	0° to 85° swiveling, 355° rotatable
INFORMATION	REFLECTOR WFL-40° EXCL.LED POWER SUPPLY 48V-DC

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1-10V or DALI or push button
ENERGY CLASS	E
CERTIFICATES	CB, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 60) / 2700K / 1041lm
TM-30 VALUES	Rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	40°
LED TECHNICS (LIGHT SOURCE)	1041lm // 8,6W // 121lm/W
LED TECHNICS (LUMINAIRE)	705lm // 9,9W // 71lm/W

Remarks

Take a look at our MAGNETIC PROFILES movie

Requirements

SPY 39 L TUBE
LED POWER SUPPLY 48V-DC

Options

DIMMABLE MODULATOR

M20/M26H - OCTAV 39 92740 MDL

29020 9230 FG

For detailed installation instructions, please consult the manual : **29020_XXX0_HAND.pdf**


FINISH YOUR SPECIFICATION

Current supply

# of Fixtures

Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.



21032 0030 SMART 48 MODULATOR PLUG-IN WD — 19


Dimtype: WDL = wireless dimmable

SMART 48

# of Fixtures


Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.



300 90 011 SMART 48 MODULATOR DIM9 — 19

Dimtype: 1-10V or DALI or push button



300 90 012 SMART 48 MODULATOR WD — 19


Dimtype: WDL = wireless dimmable

LED power supplies

# of Fixtures

Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.




300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN — 10

Dimtype: non-dimmable


M20/M26H - OCTAV 39 92740 MDL

29020 9230 FG



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN — 24


Dimtype: non-dimmable



21012 0230 LED POWER SUPPLY 48V-DC / 100W — 10

Dimtype: non-dimmable

Cutout dimension (mm): 40




21012 0240 LED POWER SUPPLY 48V-DC / 200W — 20

Dimtype: non-dimmable

Cutout dimension (mm): 40

Finish your product



24144 0020 B SPY 39 L TUBE B

24144 0020 FBR SPY 39 L TUBE FBR


24144 0020 FG SPY 39 L TUBE FG

24144 0020 GC SPY 39 L TUBE GC


24144 0020 W SPY 39 L TUBE W

COMPATIBLE COMPOSABLES

SHIFTLINE M26H profile — Available Colours




23359 0000 SLM26H - PROFILE



23359 0010 SLM26H - PROFILE 1m


M20/M26H - OCTAV 39 92740 MDL

29020 9230 FG



23359 0020 SLM26H - PROFILE 2m





23359 0030 SLM26H - PROFILE 3m



SPLITLINE M20 ST profile — Available Colours



23397 0000 SPM20 ST - PROFILE





23397 0020 SPM20 ST - PROFILE 2m






23397 0030 SPM20 ST - PROFILE 3m




SPLITLINE M20 profile — Available Colours




420 20 10 00 SPM20 - PROFILE 1m






420 20 20 00 SPM20 - PROFILE 2m





420 20 30 00 SPM20 - PROFILE 3m





23301 0000 SPM20 - PROFILE B



DELTALIGHT

M20/M26H - OCTAV 39 92740 MDL

29020 9230 FG

Notes: