




OML50 - INFORM DU HO 3280mm 8+16+8LED 94063 DIM5

31438 9435 B

BESCHIKBAAR IN
ZWART 31438 9435 B



[Bekijk op website](#)



Algemene info

LOCATIE	binnen
STOF EN WATERDICHTHEID	IP20
GEWICHT (KG)	3.3
INFO	CLUSTER DOWN: 2221lm/m CLUSTER UP: 2776lm/m INCL.DIMMABLE LED POWER SUPPLY (DALI-2 standard) CABLING 1 CIRCUIT

Elektrische info

ELEKTRISCH	220-240V / 0 50-60Hz
KLASSE	I
VOEDING INBEGREPEN	YES
DIM TYPE	DALI
ENERGIE KLASSE	D
CERTIFICATES	EPD, RCM

Info lichtbron

LIGHTSOURCE NAME	LED
LICHTBRON	DOWN: LED cluster 48,4W / CRI>90 (R9: 50) / 4000K / 7283lm UP: LED cluster 60,5W / CRI>90 (R9: 50) / 4000K / 9104lm
TM-30 WAARDEN	Rf: 90 / Rg: 101
SMD	SDCM3
RISK-GROEP	RG1
LM80	L80 > 60000
BEAMANGLE	63°
LED TECHNIEK (LICHTBRON)	DOWN: 7283lm // 48,4W // 151lm/W UP: 9104lm // 60,5W // 151lm/W

Opties

WIRELESS CONTROL DIM5

Notes: