





INFORM R3+ DOWN 93048 DIM5

REFERENCE 26821 9325 W-B

AVAILABLE IN
BLACK-BLACK 26821 9325 B-B
BLACK-FLEMISH GOLD 26821 9325 B-FG
FLEMISH GOLD-BLACK 26821 9325 FG-B
WHITE-BLACK 26821 9325 W-B
WHITE-WHITE 26821 9325 W-W



[View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Surface mounted,Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	4.2
ADJUSTABILITY	non adjustable
INFORMATION	168 x REFLECTOR WFL-71° INCL.DIMMABLE LED POWER SUPPLY 1050mA-DC
Electrical info	
ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	C
CERTIFICATES	CB, ENEC, RCM
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 33,9W / CRI>90 (R9: 50) / 3000K / 5275lm
SDCM	SDCM3
LM80	L80 > 60000
BEAMANGLE	71°
LED TECHNICS (LIGHT SOURCE)	5275lm // 33,9W // 155lm/W
LED TECHNICS (LUMINAIRE)	4405lm // 39W // 113lm/W


Options

SUSPENSION SET 32 5x0,75 1,6m
 CABLE BASE R / S
 COVERSET R 62-90-100 / S 62-80-90



For detailed installation instructions, please consult the manual : [26821_XXX5_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Current supply

	<u>203 99 55 ANO</u> CABLE BASE R ANO	☐
	<u>203 99 55 B</u> CABLE BASE R B	☐
	<u>203 99 55 W</u> CABLE BASE R W	☐
	<u>203 99 56 ANO</u> CABLE BASE S ANO	☐
	<u>203 99 56 B</u> CABLE BASE S B	☐
	<u>203 99 56 W</u> CABLE BASE S W	☐





Coversets

	<u>204 00 62 ANO</u> COVERSET R 62 ANO	☐
	<u>204 00 62 B</u> COVERSET R 62 B	☐
	<u>204 00 62 W</u> COVERSET R 62 W	☐
	<u>204 00 90 ANO</u> COVERSET R 90 ANO	☐
	<u>204 00 90 B</u> COVERSET R 90 B	☐
	<u>204 00 90 W</u> COVERSET R 90 W	☐

DELTALIGHT

INFORM R3+ DOWN 93048 DIM5

26821 9325 W-B

	<u>204 00 100 ANO</u> COVERSET R 100 ANO	☐
	<u>204 00 100 B</u> COVERSET R 100 B	☐
	<u>204 00 100 W</u> COVERSET R 100 W	☐
	<u>204 62 62 ANO</u> COVERSET S 62 ANO	☐
	<u>204 62 62 B</u> COVERSET S 62 B	☐
	<u>204 62 62 W</u> COVERSET S 62 W	☐
	<u>204 80 80 ANO</u> COVERSET S 80 ANO	☐
	<u>204 80 80 B</u> COVERSET S 80 B	☐
	<u>204 80 80 W</u> COVERSET S 80 W	☐
	<u>204 90 90 ANO</u> COVERSET S 90 ANO	☐
	<u>204 90 90 B</u> COVERSET S 90 B	☐
	<u>204 90 90 W</u> COVERSET S 90 W	☐

Suspension parts

	<u>15225 0320 B</u> SUSPENSION SET 32 5x0,75 1,6m B	☐
---	--	--------------------------

DELTALIGHT

INFORM R3+ DOWN 93048 DIM5

26821 9325 W-B

15225 0320 W SUSPENSION SET 32 5x0,75 1,6m W



Electric connection parts



15225 0360 B CONNECTION ST B



Cutout dimension (mm): 43

15225 0360 W CONNECTION ST W



Notes: