



M20/M26H - SPY 52 WALLWASH SOFT 930 MDL

19894 9000 B

AVAILABLE IN

NOIR 19894 9000 B

FLEMISH BRONZE 19894 9000 FBR

FLEMISH GOLD 19894 9000 FG

COULEUR OR 19894 9000 GC

BLANC 19894 9000 W



[View on website](#)



General info

LOCATION	interieur
INSTALLATION	Systèmes basse tension Monté sur systèmes basse tension
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.4
ADJUSTABILITY	0° à 90° inclinable, 355° rotatif
INFORMATION	WALLWASH LENS EXCL LED POWER SUPPLY 48V-DC

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = dimmable 1 à 10 V ou DALI ou bouton poussoir
ENERGY CLASS	F
CERTIFICATION	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 10,2W / CRI>90 (R9: 50) / 3000K-1800K / 1038lm
SDMC	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1038lm // 10,2W // 109lm/W
LED TECHNICS (LUMINAIRE)	490lm // 11,7W // 42lm/W

Remarks

Take a look at our [MAGNETIC PROFILES movie](#)

Requirements






LED POWER SUPPLY 48V-DC

Options

DIMMABLE MODULATOR

For detailed installation instructions, please consult the manual : [19894_XXX0_HAND.pdf](#)

FINISH YOUR SPECIFICATION

le cable d'alimentation		# of Fixtures
 web2print_power_supply_info_box		Min current Max current
	21032 0030 SMART 48 MODULATOR PLUG-IN WD Dimtype: WDL = dimmable sans fil	16 ☐
SMART 48		# of Fixtures
 web2print_power_supply_info_box		Min current Max current
	300 90 011 SMART 48 MODULATOR DIM9 Dimtype: 1 à 10 V ou DALI ou bouton poussoir	16 ☐
	300 90 012 SMART 48 MODULATOR WD Dimtype: WDL = dimmable sans fil	16 ☐
les alimentations led		# of Fixtures
 web2print_power_supply_info_box		Min current Max current
	300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN Dimtype: non dimmable	8 ☐
	300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN Dimtype: non dimmable	20 ☐




DELTALIGHT

M20/M26H - SPY 52 WALLWASH SOFT 930 MDL

19894 9000 B

	21012 0230 LED POWER SUPPLY 48V-DC / 100W	8 ☐
	Dimtype: non dimmable	
	Cutout dimension (mm): 40	
	21012 0240 LED POWER SUPPLY 48V-DC / 200W	17 ☐
	Dimtype: non dimmable	
	Cutout dimension (mm): 40	

COMPATIBLE COMPOSABLES

SHIFTLINE M26H profile	Available Colours
 23359 0000 SLM26H - PROFILE	 
 23359 0010 SLM26H - PROFILE 1m	 
 23359 0020 SLM26H - PROFILE 2m	         
 23359 0030 SLM26H - PROFILE 3m	         
SPLITLINE M20 ST profile	Available Colours
 23397 0000 SPM20 ST - PROFILE	 
 23397 0020 SPM20 ST - PROFILE 2m	 
 23397 0030 SPM20 ST - PROFILE 3m	 





DELTALIGHT

M20/M26H - SPY 52 WALLWASH SOFT 930 MDL

19894 9000 B

SPLITLINE M20 profile

Available Colours

	420 20 10 00 SPM20 - PROFILE 1m	
	420 20 20 00 SPM20 - PROFILE 2m	
	420 20 30 00 SPM20 - PROFILE 3m	
	23301 0000 SPM20 - PROFILE B	

Notes: