
DELTALIGHT




M26L - SPY 391 SOFT 93020 DIM5

REFERENCE 23438 9025 W

AVAILABLE IN
BLACK 23438 9025 B
BRUSHED ALU 23438 9025 BRA
BRUSHED ANTHRACITE 23438 9025 BRAT
BRUSHED COPPER 23438 9025 BRCU
BRUSHED GOLD 23438 9025 BRG
BRUSHED OLD BRONZE 23438 9025 BROB
FLEMISH BRONZE 23438 9025 FBR
FLEMISH GOLD 23438 9025 FG
GOLD COLOURED 23438 9025 GC
PIANO BLACK 23438 9025 PB
WHITE 23438 9025 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° to 85° swiveling, 360° rotatable
INFORMATION	REFLECTOR FL-20° EXCL.LED POWER SUPPLY 48V-DC

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	F
CERTIFICATES	EPD

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 6W / CRI>90 (R9: 50) / 3000K-1800K / 623lm
TM-30 VALUES	Rf: 90 / Rg: 99
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	20°
LED TECHNICS (LIGHT SOURCE)	623lm // 6W // 105lm/W
LED TECHNICS (LUMINAIRE)	508lm // 6,9W // 74lm/W

Requirements

SPY 39 TUBE
LED POWER SUPPLY 48V-DC

For detailed installation instructions, please consult the manual : **23438_XXX5_HAND.pdf**

DELTALIGHT

M26L - SPY 391 SOFT 93020 DIM5

23438 9025 W


FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures


Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.




300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN — 8 ☐

Dimtype: non-dimmable



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN — 20 ☐


Dimtype: non-dimmable



21012 0230 LED POWER SUPPLY 48V-DC / 100W — 8 ☐

Dimtype: non-dimmable

Cutout dimension (mm): 40




21012 0240 LED POWER SUPPLY 48V-DC / 200W — 17 ☐

Dimtype: non-dimmable

Cutout dimension (mm): 40

Finish your product



24144 0010 B SPY 39 TUBE B ☐

24144 0010 FBR SPY 39 TUBE FBR ☐

24144 0010 FG SPY 39 TUBE FG ☐

24144 0010 GC SPY 39 TUBE GC ☐

24144 0010 W SPY 39 TUBE W ☐

DELTALIGHT





M26L - SPY 391 SOFT 93020 DIM5

23438 9025 W



24144 0070 SPY 39 TUBE SBL

COMPATIBLE COMPOSABLES

SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)	Available Colours
 **23358 0000** SLM26L - PROFILE	
 **23358 0010** SLM26L - PROFILE 1m	
 **23358 0020** SLM26L - PROFILE 2m	
 **23358 0030** SLM26L - PROFILE 3m	

Notes: